

SD motor type: 1CV3133C low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) gray cast iron housing Basic Line IE3, NEMA Premium, CSA, UL, 6-pole * size 132M, * 5.5 kW (50 Hz) NEMA 60 Hz: 7.5 HP 60 Hz, P60: IE2 standard color RAL 7030 if no order code is specified for selecting another color. Purchase of this product is exclusively governed by the Innomotics T&Cs located at <https://www.innomotics.com/terms-and-conditions> 3 AC 50Hz 415VD * 3 AC 60 Hz 480 VD IM B 3, 3 PTC thermistors for disconnection (2 terminals) Terminal box at top B02=Acceptance test certificate 3.1 according to EN 10204 B61=Document, order-specific dimension drawing F01=built-on holding brake F11=Brake control voltage 230 V AC, 50/60 Hz F50=Mechanical-manual release of brake with actuating lever M11=Rating plate made of stainless steel

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)

<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com>

