

XP motor type: 1CV3280B low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) gray cast iron housing Basic Line Premium Efficiency IE3, 4-pole * size 280S * 75 kW (50 Hz), 86 kW (60 Hz) P60: IE2 Ex tc IIIB T120° Dc version for zone 22 for non-conductive dust standard color RAL 7030 if no order code is specified for selecting another color. Purchase of this product is exclusively governed by the Innomatics T&Cs located at <https://www.innomotics.com/terms-and-conditions> 3 AC 50 Hz 400 VD IM B3 3 PTC thermistors for disconnection (2 terminals) Terminal box at top B02=Acceptance test certificate 3.1 according to EN 10204 B43=Design for converter operation with operating data on voltage-source DC link converter H19=degree of protection IP66 S02=Special paint finish Y56=Paint finish in other RAL colors (for selection see catalog) RAL.. Y82=Extra rating plate with customer data (no modified motor operating data permissible)

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)

<https://support.industry.siemens.com/cs/products?mf=ps&lc=en-WW>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com>

