

SD motor type: 1CV3220B low-voltage motor, IEC squirrel-cage rotor, self-cooled, IP55 temperature class 155(F) according to 130(B) gray cast iron housing Basic Line Premium Efficiency IE3, 60 Hz, P60: IE2 4-pole \* size 225S \* 37 kW (50 Hz) 42.5 kW (60 Hz) standard color RAL 7030 if no order code is specified for selecting another color. Purchase of this product is exclusively governed by the Innomotics T&Cs located at <https://www.innomotics.com/terms-and-conditions> Non-standard winding 3 AC..Hz,..V,..kW IM B 3, without motor protection Terminal box at top B02=Acceptance test certificate 3.1 according to EN 10204 H07=Stainless screws (external) H22=Degree of protection IP56 M11=Rating plate made of stainless steel N06=Temperature class 155 (F), utilized according to 130(B), coolant temperature 50°, derating approx. 8% Q80=Extension of the liability for defects by 12 to a total of 24 months as of delivery R15=One cable gland, metal S04=Special paint finish offshore

#### Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)

<https://support.industry.siemens.com/cs/products?mf=ps&lc=en-WW>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com>

