

SITRANS FM MAG 3100 Full-bore electromagnetic flow sensor, flanged, diameter DN 15 to DN 2000 (1/2" to 78"). Suitable for volume flow measurement of liquids (conductive), main applications in process industry, chemical industry, steel industry, mining, utility, power generation and distribution, O&G/HPI. . DN200, 8 Inch ANSI B16.5, Class 150 Carbon steel flanges ASTM A 105, corrosion-resistant coating of category C4 PTFE Titanium (not for PFA) Sensor for remote transmitter (Order transmitter separately) No bus communication Metric cable glands, Polyamid terminal box or MAG 6000i integral mount Factory declaration 2.1 (EN 10204) Tag (device parameter, max. 20 characters), plate, stainless steel 304/1.4301 Customer specific transmitter setup (add plain text)

### Further information

#### Configurable Products

Technical Data and CAX data (3d-models , eplan.macros) from configurable products cannot shown here. To display the technical data for your device configuration please open PIA LifeCyclePortal and enter there your product number (MLFB). Exemplary 3d-models and eplan-macros are available at the industry imagadatabase. Data for a specific product can be requested with help of a support request.

#### PIA LifeCyclePortal

<https://pia-portal.automation.siemens.com>

#### Industry - Image Database

<http://www.automation.siemens.com/bilddb/>

#### Industry Mall (Online-Order System)

<https://mall.industry.siemens.com>

#### Information- and Downloadcenter (Catalogs, Brochures, ...)

<http://www.siemens.com/industrial-controls/catalogs>

#### Support Request

<https://support.industry.siemens.com/my/us/en/requests#createRequest>

