



Main

Range	Acti 9
Product or component type	Overvoltage release
Device short name	IMSU
Control circuit voltage	230 V AC 50/60 Hz
Threshold tripping voltage	400 V 0.07...0.2 s 350 V 0.25...0.75 s 300 V 1...5 s 275 V 3...15 s 255 V
9 mm pitches	2
Product compatibility	IC60 IID Single terminal Double terminal ISW-NA IDPN Vigji ARA RCA

Complementary

Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Height	82.5 mm
Width	18 mm
Depth	68 mm
Colour	White
Connections - terminals	Clamp terminal 1...6 mm ² rigid Clamp terminal 1 cable(s) 0.5...4 mm ² flexible
Wire stripping length	10 mm
Tightening torque	1 N.m

Environment

Standards	EN 50550
Quality labels	CE
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Period	18 months
--------	-----------