



Main

Range	Acti 9
Product or component type	Undervoltage release
Device short name	IMN
Control circuit voltage	115 V AC 400 Hz
Control type	Standard
9 mm pitches	2
Product compatibility	IC60 IID Single terminal Double terminal ISW-NA IDPN Vigī ARA RCA

Complementary

Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Width	18 mm
Colour	White
Connections - terminals	Clamp terminal 2 cable(s) 2.6 mm ² flexible with cable end Clamp terminal 1 cable(s) 5 mm ² flexible Clamp terminal 2 cable(s) 2.6 mm ² rigid Clamp terminal 1 cable(s) 7 mm ² rigid
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available Download End Of Life Manual

Contractual warranty

Period	18 months
--------	-----------