



Main

Range	Acti 9
Product or component type	Undervoltage release
Device short name	IMN
Control circuit voltage	220...240 V AC 50/60 Hz
Control type	Standard
9 mm pitches	2
Product compatibility	IC60 IID Single terminal Double terminal ISW-NA IDPN Vigi ARA RCA

Complementary

Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Width	18 mm
Colour	White
Connections - terminals	Clamp terminal 2 cable(s) 2.7 mm ² flexible with cable end Clamp terminal 1 cable(s) 6 mm ² flexible Clamp terminal 2 cable(s) 2.7 mm ² rigid Clamp terminal 1 cable(s) 8 mm ² rigid
Tightening torque	1 N.m

Environment

Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1216 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Period	18 months
--------	-----------