

# ASISSLB5

## AS-Interface - for Ø 22 emergency stop - plastic



### Main

Product or component type	Interface for Ø 22 emergency stop
Range compatibility	AS-Interface cabling system
Fixing collar material	Plastic
AS-Interface	0.B.F.F
Supply	Via AS-Interface

### Complementary

Contacts type and composition	1 NC + 1 NC
Addressing	Using adjustment terminal
[Us] rated supply voltage	24 V DC (- 15...15 %)
Power consumption	1.2 W
Current consumption	45 mA AS-Interface line
Connections - terminals	IDC for AS-Interface line
Mechanical durability	300000 cycles
Product weight	0.04 kg

### Environment

Standards	EN 954-1 category 4 EN/IEC 60204-1 EN/IEC 60947-5-1 ISO 13849-1 category 4
Product certifications	CSA TÜV UL
IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-10...55 °C
Ambient air temperature for storage	-25...85 °C
Shock resistance	10 gn
Vibration resistance	5 gn

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.