

CONNECTING CABLE S7 SHIELDED 1.0M
 CONNECTION CABLE SHIELDED FOR SIMATIC S7-1500
 BETWEEN FRONT CONNECTOR MODULE A. CONNECT.
 MODULE 50 X 0.14QMM WITH IDC CONNECTORS,LENGTH 1.0M



Figure similar

Operating data	
Operating voltage / at DC	
<ul style="list-style-type: none"> • Rated value • maximum 	24 V 60 V
Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage 	0 ... 60 °C -30 ... +70 °C
General data	
Suitability for interaction	
<ul style="list-style-type: none"> • Input card PLC • PLC output card 	Yes Yes
Suitability for use	
<ul style="list-style-type: none"> • digital signal transmission • analog signal transmission 	Yes Yes
Product properties, functions, components / general	
Number of channels	32

Wire length	1 m
Number of poles	50
Number of conductors / of connecting cable	50
Conductor cross section / Rated value	0.14 mm ²
Color / of cable sheath	Black
Outer diameter / of cable sheath	11 mm
Number of poles / at the 1st interface	50
Number of poles / at the 2nd interface	50
Certificate of suitability / cULus approval	No
Equipment marking / acc. to DIN EN 81346-2	W
Net weight	0.13 kg

last modified: 10/20/2016