## **SIEMENS**

## Data sheet

## 2XV9450-1MB11

SIMATIC MODBUS/TCP RED V2 FOR S7-400 H SYSTEMS, SINGLE LICENSE, ON CD



General information		
Engineering with		
<ul> <li>STEP 7 TIA Portal configurable/integrated as of</li> </ul>	V11	
version		
<ul> <li>STEP 7 configurable/integrated as of version</li> </ul>	From STEP 7 V5.4 and higher	
<ul> <li>PCS 7 configurable/integrated as of version</li> </ul>	PCS 7 V7.0	
Redundancy		
<ul> <li>Redundancy capability</li> </ul>	Yes; Suitable for configuring H systems	
Protocols		
SIMATIC communication		
<ul> <li>Communication as Modbus server</li> </ul>	Yes	
<ul> <li>Communication as Modbus client</li> </ul>	Yes	
<ul> <li>User data per job (of which consistent), max.</li> </ul>	250 byte	
Software		
Runtime software		
Target system		
— ET 200S	Yes	
— S7-300	Yes	

— S7-400	Yes
— WinAC	No
Block	
<ul> <li>Local data requirements</li> </ul>	302 byte
• FB length in RAM, max.	24 kbyte
Multi-instance capable	Yes
Communication data	
Multiport	Yes; Dependent on CP
<ul> <li>Master-slave coupling</li> </ul>	SIMATIC S7 as master or slave
<ul> <li>implemented function codes</li> </ul>	01, 02, 03, 04, 05, 06, 15, 16
Authorization/licenses	
• Single license (EL)	Yes
Configuration	
Configuration software	
<ul> <li>Wizard for configuration support</li> </ul>	No
Programming	
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
Configuration examples	
— STL example project	Yes
— CFC example project	Yes
Documentation	
Languages	
• German	Yes; Electronic, included on CD
• English	Yes; Electronic, included on CD
last modified:	11/22/2016