


AC2476



AS-Interface CompactLine module

CompactLine M12 4DI 4DO



Electrical data	
Operating voltage	[V] 26.5...31.6 DC; ("supply class 2" to cULus)
Max. current consumption from AS-i	[mA] 250
Max. current load total	[A] 4
Additional voltage supply	[V] 10...30 DC; (AUX)
Integrated watchdog	yes
Inputs / outputs	
Number of inputs and outputs	Number of digital inputs: 4; Number of digital outputs: 4



AS-Interface CompactLine module

CompactLine M12 4DI 4DO

Inputs					
Number of digital inputs	4; (bidirectional)				
Input circuit of digital inputs	PNP				
voltage supply [V]	20...30				
Max. total current rating of inputs [mA]	200				
Input current limitation [mA]	15				
Input current High [mA]	6...10				
Input current Low [mA]	0...2				
Min. switching level high signal [V]	11				
Digital inputs protected against short circuits	yes				
Sensor supply of the inputs	AS-i				
Outputs					
Electrical design	AS-i				
Number of digital outputs	4				
Beschaltung	PNP				
Voltage range DC	10...30; (to PELV)				
Max. current load per output [mA]	2000; (utilisation category DC-13 (control of electromagnets): 20 W (IEC 60947-5-1))				
Short-circuit proof	yes				
Electrically separated	yes				
Operating conditions					
Ambient temperature [°C]	-25...80				
Protection	IP 67; ("enclosure type 1" according to cULus; when flat cables are used E7400x / E7401x)				
Tests / approvals					
EMC	EN 50295				
AS-i classification					
AS-i version	2.11 + 3.0				
AS-i addressing	IR addressing possible				
Extended addressing mode possible	no				
AS-i profile	S-7.0.E				
AS-i I/O configuration [hex]	7				
AS-i ID code [hex]	0.E				
AS-i certificate	46001				
Assignment of the data bits	data bit	D0	D1	D2	D3
	input	1	2	3	4
	socket	I-1	I-2	I-3	I-4
	pin	2+4	2+4	2+4	2+4
	Output	1	2	3	4
	socket	O-1	O-2	O-3	O-4
	pin	4	4	4	4

AC2476



AS-Interface CompactLine module


CompactLine M12 4DI 4DO

Mechanical data		
Weight [g]	380	
Type of mounting	AS-i flat cables directly connectable	
Materials	PA; socket: brass nickel-plated; threaded inserts in the lower part: brass nickel-plated; O-ring: FKM; piercing contacts: CuSn6 nickel-plated and tin-plated;	
Displays / operating elements		
Display	operation	LED, green
	errors	LED, red
	function	LED, yellow
Accessories		
Accessories (supplied)	stainless steel sleeve for installation in case of high mechanical stress , E70402	
Remarks		
Remarks	Inputs and outputs must be electrically isolated. For loads > 20 W (max. 2 A) an external protective circuit (e.g. a diode) is required.	
Pack quantity	1 pcs.	

Electrical connection - Outputs

Outputs	
3	external voltage AUX -
4	switching output
5	functional earth (FE)
1, 2	not used

Connector: M12



Electrical connection - Inputs

Inputs	
1	Sensor supply L+
2+4	data input 1 internally bridged
3	Sensor supply L-
5	functional earth

Connector: M12

AC2476



AS-Interface CompactLine module

CompactLine M12 4DI 4DO

