


## AS-Interface control cabinet module

SmartL25 4DI 2DO R C



## Electrical data

Operating voltage	[V]	26.5...31.6 DC
Max. current consumption from AS-i	[mA]	50
Max. current load total	[A]	6; (resistive)
Integrated watchdog		yes

## Inputs / outputs

Number of inputs and outputs	Number of digital inputs: 4; Number of relay outputs: 2
------------------------------	---

## Inputs

Number of digital inputs	4
Input circuit of digital inputs	PNP
voltage supply	[V] 20...30
Max. total current rating of inputs	[mA] 500
Input current High	[mA] 6...10
Input current Low	[mA] 0...2
Min. switching level high signal	[V] 11
Digital inputs protected against short circuits	yes
Sensor supply of the inputs	external (E+/E-), to PELV

# AC2255

## AS-Interface control cabinet module

SmartL25 4DI 2DO R C



Outputs																
Voltage range DC	24; (All outputs have to be supplied with the same voltage. e.g. 2 x 240 V AC, same phase conductor, or 2 x 24 V DC )															
Voltage range AC	10...240; (All outputs have to be supplied with the same voltage. e.g. 2 x 240 V AC, same phase conductor, or 2 x 24 V DC )															
Max. current load per output [mA]	6000; (resistive)															
Number of relay outputs	2															
Short-circuit proof	no															
Electrically separated	yes															
Operating conditions																
Ambient temperature [°C]	-25...70															
Note on ambient temperature	cRUus: -25...60 °C															
Protection	IP 20															
Tests / approvals																
EMC	EN 50295 EN 50178															
MTTF [years]	410															
AS-i classification																
AS-i version	2.1															
AS-i addressing	addressing socket															
Extended addressing mode possible	yes															
AS-i profile	S-7.A.E															
AS-i I/O configuration [hex]	7															
AS-i ID code [hex]	A.E															
AS-i certificate pending	yes															
Assignment of the data bits	<table border="1"><tr><td>data bit</td><td>D0</td><td>D1</td><td>D2</td><td>D3</td></tr><tr><td>input</td><td>I-1</td><td>I-2</td><td>I-3</td><td>I-4</td></tr><tr><td>Output</td><td>O-1</td><td>O-2</td><td>-</td><td>-</td></tr></table>	data bit	D0	D1	D2	D3	input	I-1	I-2	I-3	I-4	Output	O-1	O-2	-	-
data bit	D0	D1	D2	D3												
input	I-1	I-2	I-3	I-4												
Output	O-1	O-2	-	-												
Mechanical data																
Weight [g]	172															
Type of mounting	mounting on DIN rail; string mounting possible															
Materials	PA															
Displays / operating elements																
Display	switching status operation errors	LED, yellow LED, green LED, red														
Accessories																
Accessories (optional)	COMBICON connectors															
Remarks																
Pack quantity	1 pcs.															

# AC2255



## AS-Interface control cabinet module

SmartL25 4DI 2DO R C

### Electrical connection

COMBICON:

### Connection

I-	I-	E+	E-
I1	I2	I3	I4
I+	I+	I+	I+

14	11	11	12
24	21	21	22
A+	A-		

A+	AS-i +
A-	AS-i -
I+	Sensor supply +24V
I-	Sensor supply 0V
E+	external supply +24V
E-	external supply 0V
I1...I4	switching input sensor 1...4