

CP6700-0001-0050 | 10.1-inch "Economy" Panel PC

Intel® Atom™ with up to four cores

Variants	Processor	available
CP6700-0001-0050	Intel® Atom™, 1 Core (TC3: 40*), Intel® Atom™, 2 Cores (TC3: 40*) or Intel® Atom™, 4 Cores (TC3: 50*)	yes

*The TwinCAT 3 performance class defines the exact ordering number for the respective TwinCAT 3 product. Please see [here](#) for an overview of the TC3 performance classes.

CP6700-0001-0050	
Housing	aluminium front with steel sheet rear cover
	all connectors at the bottom of the rear side
	1 slot for one CFast card accessible from the rear side
	lithium battery of the system clock, accessible from the rear side
	pull-out clamping levers for fast installation without loose parts
	protection class front side IP 54, rear side IP 20
	operating temperature 0...55 °C
Front panel	10.1-inch TFT display, resolution 1024 x 600 WSVGA
	touch screen
	without keys
Features	Intel® Atom™ E3815, 1.46 GHz, 1 core (TC3: 40)
	3½-inch motherboard for Intel® Atom™
	2 GB DDR3L RAM, expandable ex factory to 8 GB
	graphic adapter integrated inside the Intel® processor, 1 DVI-D port occupied by the display in the front and 1 DVI connector free
	on-board dual Ethernet adapter with 2 x 100/1000BASE-T connector
	4 GB CFast card, extended temperature range
	4 USB 2.0 ports
	24 V DC power supply
Microsoft Windows Embedded Compact 7, English	

Options	10.1-inch "Economy" Panel PC
C9900-C572	processor Intel® Atom™ E3827, 1.75 GHz, 2 cores (TC3: 40), instead of Intel® Atom™ E3815, 1.46 GHz (TC3: 40). With Microsoft Windows Embedded Compact 7 only one core is supported. Multicore support is available with Windows Embedded Standard 7, Windows 7 Professional, Windows 7 Ultimate and Windows 10 IoT Enterprise.
C9900-C573	processor Intel® Atom™ E3845, 1.91 GHz, 4 cores (TC3: 50), instead of Intel® Atom™ E3815, 1.46 GHz (TC3: 40). With Microsoft Windows Embedded Compact 7 only one core is supported. Multicore support is available with Windows Embedded Standard 7, Windows 7 Professional, Windows 7 Ultimate and Windows 10 IoT Enterprise.
C9900-R257	memory extension to 4 GB DDR3L RAM, instead of 2 GB, requires a 64 bit operating system or only 3 GB are addressable
C9900-R258	memory extension to 8 GB DDR3L RAM, instead of 2 GB, requires a 64 bit operating system
C9900-B415	third on-board Ethernet adapter on the 3½-inch motherboard for Intel® Atom™ or Intel® Celeron® ULV 827E 1.4 GHz, wired out with a 100/1000BASE-T connector inside the connector bracket at the connection section
C9900-H586	30 GB CFast card, 3D flash, extended temperature range, instead of 4 GB CFast card
C9900-H590	60 GB CFast card, 3D flash, extended temperature range, instead of 4 GB CFast card
C9900-H559	8 GB CFast card, SLC flash, extended temperature range, instead of 4 GB CFast card
C9900-H560	16 GB CFast card, SLC flash, extended temperature range, instead of 4 GB CFast card
C9900-H567	32 GB CFast card, SLC flash, extended temperature range, instead of 4 GB CFast card
C9900-H571	64 GB CFast card, SLC flash, extended temperature range, instead of 4 GB CFast card
C9900-U214	internal, capacitive 1-second UPS to ensure secure backup of persistent application data on the flash card, requires TwinCAT and Windows Embedded Compact 7, Windows Embedded Standard 7 or Windows 10 IoT Enterprise
C9900-S706	TwinCAT 2 PLC runtime for Windows Embedded Compact 7
C9900-S707	TwinCAT 2 NC PTP runtime for Windows Embedded Compact 7
C9900-S708	TwinCAT 2 NC I runtime for Windows Embedded Compact 7