



EJ2918 | 8-channel digital output, TwinSAFE, 24 V DC

The EJ2918 EtherCAT plug-in module is a digital output module for actuators for 24 V DC. The plug-in module has eight fail-safe outputs and meets the requirements of IEC 61508 SIL 3 and DIN EN ISO 13849 PL e.

Technical data	EJ2918
Connection technology	distribution board
Safety standard	EN ISO 13849-1:2015 (Cat. 4, PL e) and EN 61508:2010 (SIL 3)
Number of outputs	8
Protocol	TwinSAFE/Safety over EtherCAT
Max. output current	500 mA
Fault response time	≤ watchdog time (parameterisable)
Current consumption E-bus	typ. 310 mA
Bit width in the process image	input: 6 byte; output: 6...7 byte
Special features	8 safe outputs
Dimensions (W x H x D)	12 mm x 152 mm x 55 mm
Operating/storage temperature	0...+55 °C/-25...+85 °C
Relative humidity	95 %, no condensation
Permitted degree of contamination	2
Climate class EN 60721-3-3	3K3
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protection class	IP 20
Approvals	CE, TÜV SÜD

Related products	
EJ2914	EtherCAT plug-in module, 4-channel digital output, TwinSAFE, 24 V DC, 0.5 A
EJ1957	EtherCAT plug-in module, 8 fail-safe inputs, 4 fail-safe outputs, TwinSAFE, 24 V DC
EJ1914	EtherCAT plug-in module, 4-channel digital input, TwinSAFE, 24 V DC
EJ1918	EtherCAT plug-in module, 8-channel digital input, TwinSAFE, 24 V DC
EJ6910	TwinSAFE Logic