



## ELX3314 | 4-channel analog input terminal thermocouple/mV measurement, 2-wire connection, 16 bit, Ex i



The ELX3314 analog input terminals allows the direct connection of thermocouples located in hazardous areas classified Zone 0/20 or 1/21. The circuitry of the ELX3314 can operate sensors with 2-wire technology. Linearisation is possible over the entire freely selectable temperature range. The error LEDs indicate a broken wire. Compensation for the cold junction is achieved through internal temperature measurement. Millivolt measurement is also possible with ELX3314.

Technical data	ELX3314
Technology	temperature measurement
Sensor types	thermocouples type K, J, L, E, T, N, U, B, R, S, C (default: type K)
Number of inputs	4 (differential)
Connection method	2-wire
Measuring range	depending on sensor type, default type K: -200...+1350 °C, voltage measurement: $\pm 30 \dots \pm 100$ mV, for further types and details see documentation
Resolution	0.1 °C per digit
Measuring error	$< \pm 0.3$ % (relative to full scale value)
Internal resistance	typ. $\geq 10$ k $\Omega$ (differential)
Input filter limit frequency	typ. 1 kHz; depending on sensor length, conversion time, sensor type
Conversion time	10...800 ms (adjustable, default: 100 ms)
Supply voltage electronics	24 V DC (via power contacts), ELX9560 power supply
Current consumption power contacts	typ. 10 mA
Current consumption E-bus	typ. 70 mA
Special features	limit value monitoring, digital filter and characteristic curve linearisation integrated
Weight	approx. 60 g
Operating/storage temperature	-25...+60 °C/-40...+85 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. class/installation pos.	IP 20/see documentation
Approvals	CE, Ex, IECEx

further Ex components	
ELXxxxx	EtherCAT Terminals with intrinsic safe in- and output
ELXxxxx-0090	EtherCAT Terminals with intrinsic safe in- and output and TwinSAFE SC
CPXxxxx	Multi-touch Panel PCs and multi-touch Control Panels for use in hazardous areas, Zone 2/22