



EL1004 | 4-channel digital input terminal 24 V DC, 3 ms

The EL1004 digital input terminal acquires the binary control signals from the process level and transmits them, in an electrically isolated form, to the higher-level automation unit. Digital input terminals from the EL100x series have a 3 ms input filter. The EtherCAT Terminals indicate their state via an LED.

Technical data	EL1004 ES1004
Connection technology	2-wire
Specification	EN 61131-2, type 1/3
Number of inputs	4
Nominal voltage	24 V DC (-15 %/+20 %)
"0" signal voltage	-3...+5 V (EN 61131-2, type 3)
"1" signal voltage	11...30 V (EN 61131-2, type 3)
Input current	typ. 3 mA (EN 61131-2, type 3)
Input filter	typ. 3.0 ms
Distributed clocks	–
Current consumption power contacts	typ. 2 mA + load
Current consumption E-bus	typ. 90 mA
Electrical isolation	500 V (E-bus/field potential)
Bit width in the process image	4 inputs
Configuration	no address or configuration setting
Special features	standard input terminals for 2-wire connection
Weight	approx. 50 g
Operating/storage temperature	-25...+60 °C/-40...+85 °C
Relative humidity	95 %, no condensation
Vibration/shock resistance	conforms to EN 60068-2-6/EN 60068-2-27
EMC immunity/emission	conforms to EN 61000-6-2/EN 61000-6-4
Protect. class/installation pos.	IP 20/variable
Pluggable wiring	for all ESxxxx terminals
Approvals	CE, UL, Ex, IECEx

Special terminals	
EL1004-0020	4-channel digital input terminal 24 V DC, functional isolation 2500 V, (Testing voltage E-bus/field potential, production test)