

### Product type designation

Product description

### IE M12 Plug PRO (PROFINET)

M12 connector with high protection, 4-pole, D-coded

IE M12 plug PRO M12 plug-in connector with rugged metal

enclosure and quick-connect technology, 180° cable outlet (D-coded)

1 pack=8 units for SCALANCE X208 PRO and ET 200 PRO PN



### Suitability for use

For connecting electrical cables to SCALANCE X208PRO, ET200 PRO PN or ET200 eco PN, with insulation displacement contacts

### Transfer rate

Transfer rate / for Industrial Ethernet

10 Mbit/s, 100 Mbit/s

### Interfaces

Number of electrical connections

- for Industrial Ethernet FC TP cables 4
- for network components or terminal equipment 1

Type of electrical connection

- for Industrial Ethernet FC TP cables integrated cut-and-clamp contacts for 4-wire TP FC installation cable
- for network components or terminal equipment M12 connector (D-coded)

Type of electrical connection / FastConnect

No

### Mechanical data

Material / of the enclosure

metal

Locking mechanism design

Screw

Design, dimensions and weights	
Type of cable outlet	180° cable outlet
Width	14 mm
Height	14 mm
Depth	59 mm
Net weight	37 g

Ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> <li>during transport</li> </ul>	-20 ... +70 °C -40 ... +80 °C -40 ... +80 °C
Chemical resistance	
<ul style="list-style-type: none"> <li>to water</li> </ul>	resistant
Protection class IP	IP67

Product features, product functions, product components / general	
Product feature	
<ul style="list-style-type: none"> <li>silicon-free</li> </ul>	Yes
Product component	
<ul style="list-style-type: none"> <li>strain relief</li> </ul>	Yes

Standards, specifications, approvals	
Certificate of suitability	
<ul style="list-style-type: none"> <li>RoHS conformity</li> <li>UL approval</li> <li>Railway application in accordance with EN 50155</li> </ul>	Yes Yes No
Standard for structured cabling	Cat5

Further information / Internet-Links	
Internet-Link	
<ul style="list-style-type: none"> <li>to website: Selector SIMATIC NET SELECTION TOOL</li> <li>to website: Industrial communication</li> <li>to website: Industry Mall</li> <li>to website: Information and Download Center</li> <li>to website: Image database</li> <li>to website: CAx Download Manager</li> <li>to website: Industry Online Support</li> </ul>	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a> <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>last modified:</b>	12/17/2019