



Main

Range	TeSys
Device short name	GV4A
Product or component type	Auxiliary contact block
Device application	Signalling
Range compatibility	TeSys GV4 multifunction circuit breaker
Mounting location	Right side
Mounting mode	Clipped
Pole contact composition	2 NO + 2 NC
Connections - terminals	Spring terminals 1 cable(s) 0.2...1.5 mm ² solid Spring terminals 1 cable(s) 0.2...2.5 mm ² flexible without cable end Spring terminals 1 cable(s) 0.25...1.5 mm ² flexible with cable end

Complementary

[Ui] rated insulation voltage	250 V conforming to IEC 60947-1
[Ue] rated operational voltage	24...250 V AC 24...250 V DC
[Ith] conventional free air thermal current	5 A
Associated fuse rating	5 A gG conforming to IEC 60947-5-1
Mechanical durability	100000 cycles
Minimum switching current	2 mA
Minimum switching voltage	17 V
Rated operational power in VA	400 VA at 230...240 V AC-12
Rated operational power in W	50 W at 24 V DC-12

Environment

Environmental characteristic	Normal environment
------------------------------	--------------------

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes

RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------