



Main

| | |
|---------------------------|----------------------------|
| Range | Compact |
| Product name | Compact NSXm |
| Device short name | NSXm 63E |
| Product or component type | Circuit breaker |
| Device application | Protection Distribution |

Complementary

| | |
|--|---|
| [In] rated current | 63 A |
| Poles description | 3P 3d |
| Control type | Toggle |
| Mounting mode | By screws (plate) Clip-on (DIN rail) |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Breaking capacity code | E 16 kA 415 V AC |
| [Icu] rated ultimate breaking capacity | Icu 25 kA at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 Icu 16 kA at 380...415 V AC 50/60 Hz conforming to IEC 60947-2 Icu 10 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 Icu 8 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ics] rated service breaking capacity | 25 kA at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 16 kA at 380...415 V AC 50/60 Hz conforming to IEC 60947-2 10 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 8 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 8 kV IEC 60947-2 |
| [Ui] rated insulation voltage | 800 V conforming to IEC 60947-2 |
| Trip unit technology | Thermal-magnetic |
| Trip unit name | TM-D |
| Trip unit protection functions | LI |

| | |
|--|---|
| Trip unit rating | 63 A at 40 °C |
| Protection type | Short-circuit protection (magnetic) Overload protection (thermal) |
| Long time pick-up adjustment range | 0.7...1 x I _n |
| Short-time pick-up adjustment type I _{sd} | Fixed |
| Short-time delay adjustment type | Fixed |
| Magnetic hold current | 640 A |
| Magnetic tripping current | 960 A |
| Suitability for isolation | Yes conforming to IEC 60947-2 |
| Utilisation category | Category A |
| 9 mm pitches | 9 module |
| Connection pitch | 35 mm with spreaders 27 mm without spreaders |
| Connections - terminals | 1 Everlink lug wire size 2.5...95 mm ² , rigid or stranded aluminium/copper 1 Everlink lug wire size 2.5...70 mm ² , flexible copper |
| Tightening torque | 5 N.m for 2.5...10 mm ² 9 N.m for 16...95 mm ² |
| Local signalling | Flag (green)presence of auxiliary contacts: |
| Number of slots | 1 slot(s) for auxiliary switch OF 1 slot(s) for alarm switch SD 1 slot(s) for voltage release MN or MX |
| Power wire stripping length | 20 mm |

Environment

| | |
|---------------------------------------|---|
| Quality labels | CE |
| Standards | EN/IEC 60947 |
| Product certifications | CCC EAC Marine |
| Colour | Grey (RAL 7016) |
| IP degree of protection | Front cover: IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Pollution degree | 3 conforming to IEC 60947-1 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...85 °C |
| Operating altitude | 2000 m without derating 5000 m with derating |
| Mechanical durability | 20000 cycles conforming to IEC 947-1 Annex K ed 5.2 I _n |
| Electrical durability | 10000 cycles conforming to IEC 947-1 Annex F ed 5.2 for I _n at 440 V |
| Height | 137 mm |
| Width | 81 mm |
| Depth | 80 mm |
| Product weight | 1.06 kg |
| Quantity per set | Set of 1 |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

| | |
|------|---|
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
|------|---|

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|
