



### Main

Range of product	Acti 9
Product or component type	OC contact
Device short name	iOF
Signal contacts composition	1 C/O
[In] rated current	1 A: 130 V DC 1.5 A: 60 V DC 2 A: 48 V DC 6 A: 24 V DC 3 A: 415 V AC - 50/60 Hz 6 A: 240 V AC - 50/60 Hz
9 mm pitches	1

### Complementary

Range compatibility	Acti 9 iC60 Acti 9 iID double terminals residual current circuit breaker (RCCB)
Mounting mode	Clip-on
Mounting support	DIN rail
Height	86 mm
Width	9 mm
Depth	73 mm
Product weight	32 g
Colour	White
Connections - terminals	Clamp terminal1 cable(s) 0.5...2.5 mm <sup>2</sup> - flexible Clamp terminal1 cable(s) 1...4 mm <sup>2</sup> - rigid Clamp terminal2 cable(s) 2.5 mm <sup>2</sup> - rigid Clamp terminal2 cable(s) 1.5 mm <sup>2</sup> - flexible with ferrule
Wire stripping length	10 mm
Tightening torque	1 N.m

### Environment

Standards	EN/IEC 60947-5-1
-----------	------------------

Product certifications	LCIE ASEFA KEMA ASTA
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-40...85 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------