Product datasheet Characteristics

XVUZ02

fixing unit - plate with 100mm pole - black



Price*: 21.86 GBP



Main

Range of product	Harmony XVU	
Product or component type	Modular tower light	- f
Accessory / separate part type	Fixing plate	
Accessory / separate part category	Mounting and fixing accessory	900
Component name	XVU	.
Mounting diameter	60 mm	

Complementary

Pole heigth	100 mm	
Mounting support	Plate with pole	
Product compatibility	Top: AC body Top: DC body Top: swivel mounting support	
Material	PBT (polybutylene terephthalate) V-0 conforming to UL 94 ABS (acrylonitrile butadiene-styrene) PC (polycarbonate) Aluminium	
Housing colour	Black	
Connections - terminals	Push-in	
[Us] rated supply voltage	24 V AC/DC 110240 V AC	
Length	117 mm	-
Product weight	0.132 kg	

Environment

Ambient air temperature for storage	-4070 °C	_ mi
Ambient air temperature for operation	-2550 °C	S
IP degree of protection	IP65	بز ا
Product certifications	CSA UL	 - isclaime

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty


Warranty	18 months	

Product datasheet Dimensions Drawings


XVUZ02

Fixing Unit - Plate with Pole

Dimensions



Modular Tower Lights Mounting




Drawing	Part number	Part name
A1	-	Top cover
	-	Top cover (Silver)
A2	XVUC9S	Buzzer unit
	XVUC9SQ	Buzzer unit (Silver)
A3	XVUC23	Green LED unit
	XVUC24	Red LED unit
	XVUC25	Orange LED unit
	XVUC26	Blue LED unit
	XVUC27	White LED unit
	XVUC28	Yellow LED unit
A4	XVUC29	Multi-LED unit
A5	XVUC29P	Multi-LED unit, Pulse signal
A6	XVUC9V	Sound unit
A7	XVUC9VP	Sound unit, Pulse signal

Drawing	Part number	Part name
A8	XVUC020	Extender
	XVUC020Q	Extender (Silver)
A9	XVUC21B	DC body
	XVUC21BQ	DC body (Silver)
A10	XVUC21M	AC body NPN
	XVUC21MP	AC body PNP
	XVUC21MQP	AC body PNP (Silver)
A11	XVUZ06	Flexible option
A12	XVUZ01	Fixing Unit - Direct mounting (3 pins)
	XVUZ01Q	Fixing Unit - Direct mounting (Silver,3 pins)
	XVUZ03	Fixing Unit - Direct mounting (2 pins)
	XVUZ04	Fixing Unit - Direct mounting (4 pins)
A13	XVUZ02	Fixing Unit - Plate with Pole (100 mm)
	XVUZ02Q	Fixing Unit - Plate with Pole (100 mm, Silver)
	XVUZ400	Fixing Unit - Plate with Pole (400 mm)
	XVUZ800	Fixing Unit - Plate with Pole (800 mm)
A14	XVUZ05	Fixing Unit - Plate with adjustment pole (100-385 mm)
A15	XVUC43	Green LED unit, Flash
	XVUC44	Red LED unit, Flash
	XVUC45	Orange LED unit, Flash
	XVUC46	Blue LED unit, Flash
	XVUC47	White LED unit, Flash
	XVUC48	Yellow LED unit, Flash
A16	XVUZ100T	Fixing Unit - Metal bracket with pole (100 mm)
	XVUZ250T	Fixing Unit - Metal bracket with pole(250 mm)
	XVUZ400T	Fixing Unit - Metal bracket with pole (400 mm)
A17	XVUZ12	Fixing plate for use on vertical support - black

Product datasheet Mounting and Clearance

XVUZ02


Modular Tower Lights Mounting



- Gasket
- (1) (2) (3) Screw x 4 (unattached)
- M5 x (thickness+10 mm /0.39 in.)

XVUZ02

Illuminated Units, Multi-LED and Audible Units Wiring



- Fixing Unit
- Dimensions of Wiring size
- Push-in Wire Connectors
- (A) (1) (2) (3) (4) (5) Fuse: 2A,250V
- Fuse: 0.5A,125V
- Modular Tower Lights 24V AC/DC Modular Tower Lights 100...240V AC
- (6) Modular Tower Lights L1 to L5 : Illuminated LED Units