# Product datasheet Characteristics

# XVC1B2HK

tower light 100 mm 24 V siren - steady/flashing LED - orange/red



Price\*: 294.84 GBP



#### Main

		4
Range of product	Harmony XVC1	,
Product or component type	Complete pre-wired monolithic tower light	
Beacon or indicator bank unit type	2 illuminated units	\$
Sound signalling	Siren	,
Mounting diameter	100 mm	
Component name	XVC	
Light source	LED steady or flashing red LED steady or flashing orange	# 4 4 **
[Us] rated supply voltage	24 V	
Supply circuit type	DC	
Noise level	0102 dB (continuous or intermittent tone) at 1 m	

#### Complementary

Complementary		not to
Material	Polycarbonate: illuminated unit ABS (acrylonitrile butadiene-styrene): base unit PBT + ABS (UL94-V0): top cover	for and is no
Product mounting	On base	substitute
Cable cross section	0.33 mm <sup>2</sup> 0.83 mm <sup>2</sup>	s a subs
AWG gauge	AWG 18 AWG 22	 
Cable length	500 mm	not ir.
Marking	CE	on is
[Uimp] rated impulse withstand voltage	0.8 kV	 documentation
Current consumption	550 mA	- moo
Flashing frequency	0.73 Hz	_ This do
Product weight	1.78 kg	
Height	371 mm	 sclaimer:

### Environment

Standards	EN/IEC 61000-6-2 EN/IEC 61000-6-3 EN/IEC 61000-6-4
Product certifications	UL
Protective treatment	TC
Ambient air temperature for storage	-3570 °C
Ambient air temperature for operation	-2050 °C
Electrical shock protection class	Class II conforming to EN/IEC 61140
IP degree of protection	IP54 conforming to EN/IEC 60529

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	

#### Contractual warranty


Warranty	18 months	


# XVC1B2HK

## Pre-assembled and Pre-wired Tower Light with Siren

#### **Dimensions**

Below drawing shows the maximum configuration of the product. Select the number of stages according to the product characteristics in order to get b dimension.





No. of illuminated units	b in mm	b in in.
1	293	11.54
2	371	14.61
3	449	17.68

# Product datasheet Mounting and Clearance

# XVC1B2HK

# Pre-assembled and Pre-wired Tower Light with Siren

## Mounting on Horizontal Support (Direct or with Fixing Plate)

#### Panel cut-out

