



Commercial status

Discontinued: 31 May 2019

ⓘ Discontinued

Main

Range of product	Acti 9
Product name	Acti 9 IC
Product or component type	Programmable twilight switch with time switch function
Device short name	IC2000P+
Device application	Building
Provided equipment	wall-mounted cell
Load type	230 V AC halogen lamp: 2300 W 20 x 58 W dual mounted fluorescent tube with conventional ballast 10 x 100 W non-corrected fluorescent tube with conventional ballast 10 x 36 W parallel-corrected fluorescent tube with conventional ballast 10 x 100 W serial-corrected fluorescent tube with conventional ballast 2 x 100 W parallel-corrected fluorescent tube with conventional ballast 20 x 58 W non-corrected fluorescent tube with conventional ballast 20 x 58 W serial-corrected fluorescent tube with conventional ballast 26 x 36 W non-corrected fluorescent tube with conventional ballast 26 x 36 W serial-corrected fluorescent tube with conventional ballast 3 x (2 x 58 W) dual mounted fluorescent tube with electronic ballast 26 x 36 W dual mounted fluorescent tube with conventional ballast 10 x 100 W dual mounted fluorescent tube with conventional ballast 5 x (2 x 36 W) dual mounted fluorescent tube with electronic ballast 6 x 58 W fluorescent tube with electronic ballast 6 x 58 W parallel-corrected fluorescent tube with conventional ballast 7 x 11 W fluocompact lamp with electronic ballast 7 x 15 W fluocompact lamp with electronic ballast 7 x 20 W fluocompact lamp with electronic ballast 9 x 7 W fluocompact lamp with electronic ballast 9 x 36 W fluorescent tube with electronic ballast parallel-corrected mercury and sodium vapour lamps: 250 VA 230 V AC incandescent lamp: 2600 W
Battery type	Lithium
Language	French Spanish Dutch Finnish Swedish Portuguese German Italian

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Complementary

Number of channels	1
Power consumption in VA	3 VA
[Ue] rated operational voltage	230 V AC +10 % -15 % at 50/60 Hz
Maximum switching current	10 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1
Electrical insulation class	Class II
Maximum number of switchings	42
Minimum interval duration	1 min
Function available	Coupling with time switch functions Automatic time changeover
Control type	By brightness detection
Display type	Backlit LCD
Time delay range	80 s (by default) 20...140 s (on closing) 20...140 s (on contact breaking)
Backup time	5...6 years time and program saving
Type of setting	Weekly programming
Light intensity adjustment	350...2100 lux 2...50 lux 60...300 lux
Connections - terminals	1 x 6 mm ² screw terminal
Cable stiffness	Flexible Rigid
Mounting support	DIN rail
9 mm pitches	5
Height	83.5 mm
Width	45 mm
Depth	65 mm
Product weight	323 g
Market segment	Residential Small commercial
Compatibility code	IC2000P+

Environment

Ambient air temperature for operation	-20...50 °C
IP degree of protection	IP20 B IP55
Standards	EN 60730-1 EN 60529

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------

15483 is replaced by:



IC CCT15483

Acti 9 IC2000p+ (2 - 2000 lux) programmable twilight switch

Qty 1

Reason for Substitution: End of life | Substitution date: 22 October 2019