



Model Number

SJ2-N

ATEX version

Features

- 2 mm slot width
- Usable up to SIL 2 acc. to IEC 61508

Technical Data

General specifications

| | |
|------------------------------|------------------------|
| Switching function | Normally closed (NC) |
| Output type | NAMUR |
| Slot width | 2 mm |
| Depth of immersion (lateral) | 5 ... 7 mm , typ. 6 mm |
| Output type | 2-wire |

Nominal ratings

| | | |
|------------------------------|-------|---|
| Nominal voltage | U_o | 8.2 V (R_i approx. 1 k Ω) |
| Operating voltage | U_B | 5 ... 25 V |
| Switching frequency | f | 0 ... 5000 Hz |
| Hysteresis | H | 0.005 ... 0.2 |
| Suitable for 2:1 technology | | yes, Reverse polarity protection diode not required |
| Current consumption | | |
| Measuring plate not detected | | ≥ 3 mA at nominal voltage |
| Measuring plate detected | | ≤ 1 mA at nominal voltage |

Functional safety related parameters

| | |
|------------------------------|--------|
| Safety Integrity Level (SIL) | SIL 2 |
| MTTF _d | 9320 a |
| Mission Time (T_M) | 20 a |
| Diagnostic Coverage (DC) | 0 % |

Ambient conditions

| | |
|---------------------|---------------------------------|
| Ambient temperature | -25 ... 100 °C (-13 ... 212 °F) |
|---------------------|---------------------------------|

Mechanical specifications

| | |
|----------------------|------------------------------|
| Connection type | flexible leads LIFYW, 500 mm |
| Core cross-section | 0.06 mm ² |
| Housing material | PBT |
| Degree of protection | IP67 |

General information

| | |
|---------------------------|-------------------------|
| Use in the hazardous area | see instruction manuals |
|---------------------------|-------------------------|



Compliance with standards and directives

| | |
|---------------------|---|
| Standard conformity | |
| NAMUR | EN 60947-5-6:2000 IEC 60947-5-6:1999 |
| Standards | EN 60947-5-2:2007 EN 60947-5-2/A1:2012 IEC 60947-5-2:2007 IEC 60947-5-2 AMD 1:2012 |


Approvals and certificates

| | |
|--------------------|--|
| EAC conformity | TR CU 012/2011 |
| FM approval | |
| Control drawing | 116-0165 |
| UL approval | cULus Listed, General Purpose |
| Ordinary Location | E87056 |
| Hazardous Location | E501628 |
| Control drawing | 116-0453 |
| CSA approval | cCSAus Listed, General Purpose |
| CCC approval | CCC approval / marking not required for products rated ≤36 V |

Dimensions



Electrical Connection



Data for application in connection with hazardous areas

| | |
|----------------------------|-------------------|
| Equipment protection level | Ga , Gb , Da , Mb |
|----------------------------|-------------------|

Equipment protection level Ga

| | |
|--------------------|------------------|
| Type of protection | intrinsic safety |
| CE marking | CE 0102 |

Certificates

| | |
|-------------------|---|
| Appropriate type | SJ2-N... |
| ATEX certificate | PTB 99 ATEX 2219 X |
| ATEX marking | Ⓔ II 1G Ex ia IIC T6...T1 Ga |
| Standards | EN 60079-0:2012+A11:2013 , EN 60079-11:2012 |
| IECEX certificate | IECEX PTB 11.0091X |
| IECEX marking | Ex ia IIC T6...T1 Ga |
| Standards | IEC 60079-0:2011 , IEC 60079-11:2011 |

| | | |
|--------------------------------|-------|---|
| Effective internal capacitance | C_i | ≤ 30 nF A cable length of 10 m is considered. |
|--------------------------------|-------|---|

| | | |
|-------------------------------|-------|---|
| Effective internal inductance | L_i | ≤ 100 μ H A cable length of 10 m is considered. |
|-------------------------------|-------|---|

| | |
|---|--|
| Maximum permissible ambient temperature T_{amb} | Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. |
|---|--|

| | |
|----------|--|
| for ATEX | <p>at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 34$ mW , T6 : 56 °C (132.8 °F) T5 : 68 °C (154.4 °F) T4 : 96 °C (204.8 °F) T3 : 96 °C (204.8 °F) T2 : 96 °C (204.8 °F) T1 : 96 °C (204.8 °F)</p> <p>at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 64$ mW , T6 : 49 °C (120.2 °F) T5 : 61 °C (141.8 °F) T4 : 89 °C (192.2 °F) T3 : 89 °C (192.2 °F) T2 : 89 °C (192.2 °F) T1 : 89 °C (192.2 °F)</p> <p>at $U_i = 16$ V , $I_i = 52$ mA , $P_i = 169$ mW , T6 : 28 °C (82.4 °F) T5 : 40 °C (104 °F) T4 : 68 °C (154.4 °F) T3 : 68 °C (154.4 °F) T2 : 68 °C (154.4 °F) T1 : 68 °C (154.4 °F)</p> <p>at $U_i = 16$ V , $I_i = 76$ mA , $P_i = 242$ mW , T6 : 13 °C (55.4 °F) T5 : 25 °C (77 °F) T4 : 53 °C (127.4 °F) T3 : 53 °C (127.4 °F) T2 : 53 °C (127.4 °F) T1 : 53 °C (127.4 °F)</p> |
|----------|--|

| | |
|-----------|--|
| for IECEX | <p>at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 34$ mW , T6 : 73 °C (163.4 °F) T5 : 88 °C (190.4 °F) T4 : 100 °C (212 °F) T3 : 100 °C (212 °F) T2 : 100 °C (212 °F) T1 : 100 °C (212 °F)</p> <p>at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 64$ mW , T6 : 67 °C (152.6 °F) T5 : 82 °C (179.6 °F) T4 : 100 °C (212 °F) T3 : 100 °C (212 °F) T2 : 100 °C (212 °F) T1 : 100 °C (212 °F)</p> <p>at $U_i = 16$ V , $I_i = 52$ mA , $P_i = 169$ mW , T6 : 45 °C (113 °F) T5 : 60 °C (140 °F) T4 : 78 °C (172.4 °F) T3 : 78 °C (172.4 °F) T2 : 78 °C (172.4 °F) T1 : 78 °C (172.4 °F)</p> <p>at $U_i = 16$ V , $I_i = 76$ mA , $P_i = 242$ mW , T6 : 30 °C (86 °F) T5 : 45 °C (113 °F) T4 : 57 °C (134.6 °F) T3 : 57 °C (134.6 °F) T2 : 57 °C (134.6 °F) T1 : 57 °C (134.6 °F)</p> |
|-----------|--|

Equipment protection level Gb

| | | |
|---|---|---|
| Type of protection | intrinsic safety | |
| CE marking | CE 0102 | |
| Certificates | | |
| Appropriate type | SJ2-N... | |
| ATEX certificate | PTB 99 ATEX 2219 X | |
| ATEX marking | Ex II 1G Ex ia IIC T6...T1 Ga | |
| Standards | EN 60079-0:2012+A11:2013 , EN 60079-11:2012 | |
| IECEX certificate | IECEX PTB 11.0091X | |
| IECEX marking | Ex ia IIC T6...T1 Ga | |
| Standards | IEC 60079-0:2011 , IEC 60079-11:2011 | |
| Effective internal capacitance | C_i | ≤ 30 nF A cable length of 10 m is considered. |
| Effective internal inductance | L_i | ≤ 100 μ H A cable length of 10 m is considered. |
| Maximum permissible ambient temperature T_{amb} | Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 34$ mW , T6 : 73 °C (163.4 °F) T5 : 88 °C (190.4 °F) T4 : 100 °C (212 °F) T3 : 100 °C (212 °F) T2 : 100 °C (212 °F) T1 : 100 °C (212 °F) at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 64$ mW , T6 : 67 °C (152.6 °F) T5 : 82 °C (179.6 °F) T4 : 100 °C (212 °F) T3 : 100 °C (212 °F) T2 : 100 °C (212 °F) T1 : 100 °C (212 °F) at $U_i = 16$ V , $I_i = 52$ mA , $P_i = 169$ mW , T6 : 45 °C (113 °F) T5 : 60 °C (140 °F) T4 : 78 °C (172.4 °F) T3 : 78 °C (172.4 °F) T2 : 78 °C (172.4 °F) T1 : 78 °C (172.4 °F) at $U_i = 16$ V , $I_i = 76$ mA , $P_i = 242$ mW , T6 : 30 °C (86 °F) T5 : 45 °C (113 °F) T4 : 57 °C (134.6 °F) T3 : 57 °C (134.6 °F) T2 : 57 °C (134.6 °F) T1 : 57 °C (134.6 °F) | |

Equipment protection level Da

| | | |
|---|--|---|
| Type of protection | intrinsic safety | |
| CE marking | CE 0102 | |
| Certificates | | |
| Appropriate type | SJ2-N... | |
| ATEX certificate | PTB 99 ATEX 2219 X | |
| ATEX marking | Ex II 1D Ex ia IIIC T135°C Da | |
| Standards | EN 60079-0:2012+A11:2013 , EN 60079-11:2012 | |
| IECEX certificate | IECEX PTB 11.0091X | |
| IECEX marking | Ex ia IIIC T135°C Da | |
| Standards | IEC 60079-0:2011 , IEC 60079-11:2011 | |
| Effective internal capacitance | C_i | ≤ 30 nF A cable length of 10 m is considered. |
| Effective internal inductance | L_i | ≤ 100 μ H A cable length of 10 m is considered. |
| Maximum permissible ambient temperature T_{amb} | Also observe the maximum permissible ambient temperature stated in the general technical data. Keep to the lower of the two values. at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 34$ mW : 100 °C (212 °F) at $U_i = 16$ V , $I_i = 25$ mA , $P_i = 64$ mW : 100 °C (212 °F) at $U_i = 16$ V , $I_i = 52$ mA , $P_i = 169$ mW : 78 °C (172.4 °F) at $U_i = 16$ V , $I_i = 76$ mA , $P_i = 242$ mW : 57 °C (134.6 °F) | |

Equipment protection level Mb

| | | |
|--------------------------------|--------------------------------------|---|
| Type of protection | intrinsic safety | |
| Certificates | | |
| Appropriate type | SJ2-N... | |
| IECEX certificate | IECEX PTB 11.0091X | |
| IECEX marking | Ex ia I Mb | |
| Standards | IEC 60079-0:2011 , IEC 60079-11:2011 | |
| Effective internal capacitance | C_i | ≤ 30 nF A cable length of 10 m is considered. |
| Effective internal inductance | L_i | ≤ 100 μ H A cable length of 10 m is considered. |

Maximum permissible ambient temperature T_{amb}

Also observe the maximum permissible ambient temperature stated in the general technical data.
Keep to the lower of the two values.

at $U_i = 16\text{ V}$, $I_i = 25\text{ mA}$, $P_i = 34\text{ mW}$: 100 °C (212 °F)

at $U_i = 16\text{ V}$, $I_i = 25\text{ mA}$, $P_i = 64\text{ mW}$: 100 °C (212 °F)

at $U_i = 16\text{ V}$, $I_i = 52\text{ mA}$, $P_i = 169\text{ mW}$: 78 °C (172.4 °F)

at $U_i = 16\text{ V}$, $I_i = 76\text{ mA}$, $P_i = 242\text{ mW}$: 57 °C (134.6 °F)