SIEMENS

Product data sheet

3NA3832




LV HRC FUSE LINK GL/GG WITH NON-INSULATED GRIP LUGS WITH FRONT INDICATOR SIZE 00, 125A, AC 500V/DC 250V


Similar to image

Current / for AC / rated value Operating class of the fuse link Size of the fallback-system / acc. to DIN EN 60269-1	A	125 gG	
		gG	
Size of the fallback-system / acc. to DIN EN 60269-1			
		NH00	
Supply voltage			
• for AC / rated value	V	500	
• for DC	V	250	
Switching capacity current			
• in accordance with IEC 60947-2 / rated value	kA	120	
• with DC / in accordance with IEC 60947-2 / rated value	kA	25	
Design of an identification indicator		Front indicators	
type of the assembly		Non-insulated grip lugs	
Protection class IP		IP20, with connected conductors	
Climatic class		-20 to +50 at 95% relative humidity	
Ambient temperature			
• minimum	°C	-5	
• maximum	°C	40	
Product description		Using screw adapter or adapter sleeves	

Certificates/approvals:

General Product Approval		Declaration of Conformity	Test Certificates		
GOST	KEMA		EG-Konf.	Special Test Certificate	Type Test Certificates/Test Report
Shipping Approval	other				
GL®	Environmental Confirmations				
GL					
http://www.siemens.cc Industry Mall (Online http://www.siemens.cc	ordering system)	<u>js</u>			
•• •		Characteristics, FAQ //view/en/3NA3832/all	ls,)		
•	•	nension drawings, 3D /cax_en.aspx?mlfb=3N	models, device circuit d A3832	diagrams,)	
CAx-Online-Generato					
Tender specification					





last change:

Jan 28, 2013