



FUSE SWITCH DISCONNECTOR 3POLE SWITCHABLE,
 SIZE 00 I=160A,
 U=AC690V FLAT TERMINAL M8 FOR CABLE LUG 1X10-95
 MM2

Similar to image

General technical details:

Suitability for installation		Plant protection
Number of poles		3
Continuous current		
• rated value	A	160
• at 35 °C / rated value	A	160
• at 40 °C / rated value	A	152
• at 45 °C / rated value	A	144
• at 50 °C / rated value	A	136
• at 55 °C / rated value	A	128
• at 60 °C / rated value	A	120
• at 65 °C / rated value	A	112
• at 70 °C / rated value	A	110.5
Type from device		fixed mounting
Insulation voltage / rated value	V	800
Operating voltage		
• at 50/60 Hz / for AC / rated value	V	690
• for DC / rated value	V	440
Operating current		

<ul style="list-style-type: none"> • at AC-21 B <ul style="list-style-type: none"> • at 400 V / rated value • at 500 V / rated value • at 690 V / rated value • at AC-22 B <ul style="list-style-type: none"> • at 400 V / rated value • at 500 V / rated value • at 690 V / rated value • at AC-23 B <ul style="list-style-type: none"> • at 400 V / rated value 	A	160
	A	160
	A	160
	A	160
	A	160
	A	100
	A	160
Fuse system		LV HRC fuse
Installation size of fuse-link		NH000, NH00
Active power loss / maximum	W	18
Protection class IP / on the front		IP30
Product component <ul style="list-style-type: none"> • undervoltage release mechanism • undervoltage release with leading contact • Voltage trigger 		No No No
Design of the safety monitoring		No
Number of the transformers		0
Arrangement of electrical connectors / for main current circuit		Screw terminals
Design of the electrical connection / for main current circuit		screw-type terminals
Center line spacing <ul style="list-style-type: none"> • 40 mm • 50 mm • 60 mm • 100 mm • 185 mm 	mm	185 No No No No Yes
mounting position		vertical
Width	mm	49
Height	mm	647
Depth	mm	150
Ambient temperature <ul style="list-style-type: none"> • during operating 	°C	-25 ... +55
Item designation / according to DIN EN 81346-2		Q
Reference code / according to DIN EN 61346-2		Q

Certificates/approvals:

General Product Approval



CCC



GOST

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3NJ4103-3BF01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NJ4103-3BF01/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NJ4103-3BF01

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Jul 14, 2014