



TM-xB15 S24-01 FOR ET 200S XB1/XB2/XB5 TERMINAL MODULE FOR MOUNTING RIGHT NEXT TO DS1-X,RS1-X DS1E-X,RS1E-X,DSS1E-X

General technical data:		
<b>Product designation</b>		Terminal module
<b>Product-type designation</b>		TM-xB15 S24-01
<b>Design of the product</b>		for brake control modules xB1, xB2, xB5
<b>Mounting height</b>	mm	196.5
<b>Installation width</b>	mm	15
<b>Mounting depth</b>	mm	95
<b>Protection class IP</b>		IP20
<b>Impulse voltage resistance / rated value</b>	V	8,000
<b>Operating current / rated value</b>	A	4
<b>Type of the connectable conductor cross-sections</b>		
<ul style="list-style-type: none"> <li>• solid</li> <li>• finely stranded / with wire end processing</li> <li>• for AWG conductors                             <ul style="list-style-type: none"> <li>• solid</li> <li>• stranded</li> </ul> </li> </ul>		1x (0.14 ... 2.5 mm <sup>2</sup> ) 1x (0.14 ... 1.5 mm <sup>2</sup> ), acc. to IEC 60947  1x (18 ... 22) 1x (18 ... 22)
Mounting/fixing:		
<b>Dimension de la tête de tournevis</b>		Standard screwdriver Size 1
<b>Tightening torque</b>		
<ul style="list-style-type: none"> <li>• with screw-type terminals</li> </ul>	N-m	0.4 ... 0.7

**Further information:**

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrial-controls/mall>

**Cax online generator:**

<http://www.siemens.com/cax>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3RK1903-0AG00/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3RK1903-0AG00](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RK1903-0AG00)



**last change:**

Mar 5, 2013