



CONTACT. 3-PH. 4 KW/400 V, 1NO,
24 V AC 60 HZ 3-POLE, SIZE S00,
SCREW CONNECTION

| General technical data: | | |
|---|----|-------------|
| product brand name | | SIRIUS |
| Size of the contactor | | S00 |
| Protection class IP / on the front | | IP20 |
| Degree of pollution | | 3 |
| Installation altitude / at a height over sea level / maximum | m | 2,000 |
| Ambient temperature / during operating | °C | -25 ... +60 |
| Mechanical operating cycles as operating time | | |
| • of the contactor / typical | | 30,000,000 |
| • of the contactor with added auxiliary switch block / typical | | 10,000,000 |
| • of the contactor with added electronics-compatible auxiliary switch block / typical | | 5,000,000 |
| Main circuit: | | |
| Number of NC contacts / for main contacts | | 0 |
| Number of NO contacts / for main contacts | | 3 |
| Operating current | | |
| • at AC-1 / at 400 V | | |
| • at 40 °C ambient temperature / rated value | A | 22 |
| • at AC-3 / at 400 V / rated value | A | 9 |
| • at AC-4 / at 400 V / rated value | A | 8.5 |

| | | |
|--|----|-------|
| • with 1 current path / at DC-1 | | |
| • at 24 V / rated value | A | 20 |
| • at 110 V / rated value | A | 2.1 |
| • with 2 current paths in series / at DC-1 | | |
| • at 24 V / rated value | A | 20 |
| • at 110 V / rated value | A | 12 |
| • with 3 current paths in series / at DC-1 | | |
| • at 24 V / rated value | A | 20 |
| • at 110 V / rated value | A | 20 |
| • with 1 current path / at DC-3 / at DC-5 | | |
| • at 24 V / rated value | A | 20 |
| • at 110 V / rated value | A | 0.15 |
| • with 2 current paths in series / at DC-3 / at DC-5 | | |
| • at 24 V / rated value | A | 20 |
| • at 110 V / rated value | A | 0.35 |
| • with 3 current paths in series / at DC-3 / at DC-5 | | |
| • at 24 V / rated value | A | 20 |
| • at 110 V / rated value | A | 20 |
| Service power | | |
| • at AC-2 / at 400 V / rated value | kW | 4 |
| • at AC-3 / at 400 V / rated value | kW | 4 |
| • at AC-4 / at 400 V / rated value | W | 4,000 |

| Control circuit: | | |
|---|-----|-------------|
| Voltage type / of control feed voltage | | AC |
| Operating range factor control supply voltage rated value / of the magnet coil | | |
| • at 60 Hz | | |
| • for AC | | 0.8 ... 1.1 |
| Apparent pull-in power / of the solenoid / for AC | V·A | 31.7 |
| Apparent holding power / of the solenoid / for AC | V·A | 5.1 |
| Inductive power factor / with the pull-in power of the coil | | 0.77 |
| Inductive power factor / with the pull-in power of the coil | | 0.27 |

| Auxiliary circuit: | | |
|---|--|---|
| Contact reliability / of the auxiliary contacts | | 1 faulty switching per 100 million (17 V, 1 mA) |
| Number of NC contacts / for auxiliary contacts / instantaneous switching | | 0 |
| Number of NO contacts / for auxiliary contacts / instantaneous switching | | 1 |

| Short-circuit: | | |
|----------------|--|--|
|----------------|--|--|

| | | |
|--|--|--|
| Design of the fuse link <ul style="list-style-type: none"> • for short-circuit protection of the auxiliary switch / required • for short-circuit protection of the main circuit <ul style="list-style-type: none"> • with type of assignment 1 / required • at type of coordination 2 / required | | fuse gL/gG: 10 A fuse gL/gG: 35 A fuse gL/gG: 20 A |
|--|--|--|

Installation/mounting/dimensions:

| | | |
|---|----|--|
| Mounting type | | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022 |
| series installation | | Yes |
| Width | mm | 45 |
| Height | mm | 57.5 |
| Depth | mm | 72 |
| Distance, to be maintained, to earthed part / sideways | mm | 6 |

Connection type:

| | | |
|---|--|--|
| Design of the electrical connection <ul style="list-style-type: none"> • for main current circuit • for auxiliary and control current circuit | | screw-type terminals screw-type terminals |
| Type of the connectable conductor cross-section <ul style="list-style-type: none"> • for main contacts <ul style="list-style-type: none"> • solid • finely stranded <ul style="list-style-type: none"> • with conductor end processing • for AWG conductors / for main contacts • for auxiliary contacts <ul style="list-style-type: none"> • solid • finely stranded <ul style="list-style-type: none"> • with conductor end processing • for AWG conductors / for auxiliary contacts | | 2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²), max. 2x (0.75 ... 4 mm ²) 2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²) 2x (20 ... 16), 2x (18 ... 14), 1x 12 2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²), max. 2x (0.75 ... 4 mm ²) 2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²) 2x (20 ... 16), 2x (18 ... 14), 1x 12 |

Certificates/approvals:

General Product Approval

Functional Safety / Safety of Machinery

Declaration of Conformity



[Type Examination](#)



Test Certificates

[Special Test
Certificate](#)

Shipping Approval



Shipping Approval

other



[Confirmation](#)

[other](#)

[Environmental
Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:


<http://www.siemens.com/cax>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RT1016-1AC11/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RT1016-1AC11





last change:

Aug 4, 2014