

RS485 - Y-COPPER CONNECT. CABLE FOR CONNECTING A DEVICE WITH 9-PIN SUB-D CONNECTOR (SOCKET) AND EXTENSION OF THE BUS (9-PIN SOCKET),2-CORE,SHIELDED, LENGTH: 3M



Figure similar

General technical data	
AWG number	30
Model	
product designation	RS485 bus cable system 7XV5103
Mechanical Design	
length	3 m
type of plug connector / 1	D-sub connector plug, 9-pole
type of plug connector / 2	D-sub socket, 9-pole
type of plug connector	D-sub (9-pole)
color / of cable sheath	gray/white
design of the anti-kink sleeve	metalized, shielded connector housings with reduced flush mounting depth and strain relief
cable design	twisted pairs, shielded (STP)
contact assignment	3, 8
Further information	

Information- and Downloadcenter (catalogues, leaflets,...)
<http://www.siemens.com/energy-automation>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7XV5103-0AA03>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7XV5103-0AA03>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7XV5103-0AA03

Tender specifications

<http://www.siemens.com/specifications>