

SURGE SUPPRESSOR, DIODE COMBINATION,
DC 24 V, FOR MOTOR CONTACTORS SZ S0,

General technical data:

product brand name		SIRIUS
product designation		surge suppressor
Size of the contactor		S0
Design of the surge suppressor		with diode assemblies
Ambient temperature		
<ul style="list-style-type: none"> during storage 	°C	-40 ... +80
<ul style="list-style-type: none"> during operating 	°C	-25 ... +60

Control circuit:

Type of voltage / of the controlled supply voltage		DC
Control supply voltage / 1		
<ul style="list-style-type: none"> for DC 		
<ul style="list-style-type: none"> rated value 	V	24

Installation/mounting/dimensions:

mounting position		any
Type of mounting		clip-on
Width	mm	30
Height	mm	19
Depth	mm	12

Certificates/approvals:

Verification of suitability

CE / UL / CSA / CCC

General Product Approval

Declaration of Conformity

Test Certificates



CSA



GOST



UL



EG-Konf.

[Special Test Certificate](#)

Shipping Approval



ABS



BUREAU
VERITAS



DNV



GL



LRS



PRS

Shipping Approval

other



RINA



RMRS

[Confirmation](#)



VDE

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator




<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RT2926-1ER00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RT2926-1ER00



last change:

Jan 21, 2013