## SIEMENS

## **Product data sheet**

## 3RT2926-1ES00




SURGE SUPPRESSOR, DIODE COMBINATION, DC 30...250V, FOR MOTOR CONTACTORS SZ S0,

General technical data:		
product brand name	_	SIRIUS
product designation		surge suppressor
Size of the contactor		S0
Design of the surge suppressor		with diode assemblies
Ambient temperature		
during storage	°C	-40 +80
during operating	°C	-25 +60
Control circuit:		
Type of voltage / of the controlled supply voltage		DC
Control supply voltage / 1		
• for DC		
• initial rated value	V	30
final rated value	V	250
Installation/mounting/dimensions:		
mounting position		any
Type of mounting		clip-on
Width	mm	30
Height	mm	19

Depth			mm 12			
Certificates/appro	vals:					
Verification of suitability		CE	/ UL / CSA / CCC			
General Product Approval			Declaration of Conformity	Test Certificates	Test Certificates	
(SA)	GOST		EG-Konf.	Special Test Certificate		
Shipping Approval	I					
ABS	BUREAU VERITAS	ĴŠ DNV DNV	GL	Lloyd's Kegister Irs	PRS	
Shipping Approval	l	other				
RINA	RMRS	<u>Confirmation</u>	VDE			
Further information	on:					
Information- and Do		alogs, Brochures,) s/catalogs				
Industry Mall (Online http://www.siemens.c						
CAx-Online-Generat http://www.siemens.c						
••••		s, Characteristics, FAQ W/view/en/3RT2926-1ES				

http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=3RT2926-1ES00



last change:

Jan 21, 2013