

PNOZ s11 C 24VDC 8 n/o 1 n/c

751111



PNOZsigma contact expansion, outputs: 8 N/O, 1 N/C, UB = 24 V DC, width: 45 mm, plug-in spring-loaded terminals, contact block for contact expansion in connection with safety-related control components.

Technical details

| | |
|--|--|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;CCC |
| Application options: | Instantaneous contact expansion |
| Supply voltage (V): | 24,0 |
| Max. current at DC1: | 6.0 A |
| Voltage at AC1: | 240 V |
| Terminal type: | Spring-loaded terminal |
| Terminal style: | Plug-in |
| Standards: | EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1 |
| Operating modes: | Single-channel;without detection of shorts across contacts |
| Number of instantaneous safety contacts: | 8 |
| Number of instantaneous safety outputs: | 0 ST |
| Width dimension: | 45.0 mm |
| Height dimension: | 100.0 mm |
| Depth dimension: | 120.0 mm |
| Gross weight: | 350 g |
| Net weight: | 335 g |
| Ambient temperature: | -10 - 55 °C |

Optional accessories



750020

PNOZ s connector (10 pieces)



751012

PNOZ s Set2spring loaded terminals 45mm