

PNOZ e2.2p C 24VDC 2so

784135



Safety relay (standalone) Inputs: Requirement class IIIA in accordance with EN 574 Outputs: 3 N/O, 1 N/C, 2 semiconductor. Automatic start UB 24 V DC, width: 22.5 mm, plug-in spring-loaded terminals Electronic two-hand safety relay.

Technical details

| | |
|---|---|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV |
| Application options: | Two-hand monitoring Type III A |
| Operating modes: | Automatic reset;Dual-channel;Detection of shorts across contacts;Self test;with AND input;With OR input |
| Product standard: | EN 60947-5-1 |
| Standards: | EN 574 TYP III A;EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1 |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Terminal type: | Spring-loaded terminal |
| Terminal style: | Plug-in |
| Number of instantaneous safety outputs: | 2 ST |
| Number of test pulse outputs: | 2 |
| Stop category: | 0 |
| Width dimension: | 22.5 mm |
| Height dimension: | 101.0 mm |
| Depth dimension: | 121.0 mm |
| Gross weight: | 145 g |
| Net weight: | 130 g |
| Ambient temperature: | -10 - 55 °C |

Optional accessories



374290

PNOZ X Set spring loaded terminals P1+P2



774195

Terminal block filter 1



774196

Terminal block filter 2