

FIXED-MOUNTED CIRCUIT BREAKER 3-POLE,  
 SIZE I, IEC IN=630A TO 690V,  
 AC50/60HZ ICU=55KA AT 500V FRNT.CONN. TOP/BOT.  
 SINGLE-HOLE

**General technical data:**

Number of poles	3
-----------------	---

**Connections:**

Arrangement of electrical connectors	main connection front, single hole
<ul style="list-style-type: none"> <li>for main current circuit</li> </ul>	

**Certificates/approvals:**

General Product Approval	EMC	Declaration of Conformity
--------------------------	-----	---------------------------



**Shipping Approval**



**other**

[other](#)

[Environmental Confirmations](#)

**Further information:**

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/lowvoltage/maill>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3WL1106-2..33-..../all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3WL1106-2..33-....](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1106-2..33-....)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

last change:

Feb 9, 2013