

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2222C

SIMOTICS SD - 225 M - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_i/I_N	M_A/M_N T_i/T_N	M_k/M_N T_B/T_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
230	Δ	50	30.00	-/-	99.00	980	290.0	91.7	92.5	92.3	0.83	0.79	0.70	5.6	2.5	2.7	IE2
400	Y	50	30.00	-/-	57.00	980	290.0	91.7	92.5	92.3	0.83	0.79	0.70	5.6	2.5	2.7	IE2
460	Y	60	36.00	-/-	59.00	1175	295.0	91.7	92.5	92.5	0.84	0.81	0.73	5.7	2.3	2.5	IE1
460	Y	60	30.00	-/-	49.00	1182	240.0	93.0	93.3	92.6	0.83	0.79	0.69	7.0	2.9	3.1	IE2

IM B3 / IM 1001	FS 225 M	300 kg	IP55	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
Environmental conditions : -20 °C - + °C / 1,000 m				Locked rotor time (hot / cold) : 25.7 s 40.7 s	

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	65.0 / 78.0 dB(A) ²⁾	66.0 / 79.0 dB(A) ²⁾	External earthing terminal	Yes (standard)
Moment of inertia	0.5800 kg m ²		Vibration severity grade	A
Bearing DE NDE	6213 Z C3	6213 Z C3	Insulation	155(F) to 155(F)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	35.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	27.0 mm - 35.0 mm
Type of terminal box	TB1 L01	Cable entry	2xM50x1,5
Contact screw thread	M8	Cable gland	2 plugs

Notes:
 I_A/I_N = locked rotor current / current nominal
 M_k/M_N = locked rotor torque / torque nominal
 M_k/M_N = break down torque / nominal torque
 1) L10mh according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>			
SIEMENS	document type datasheet	document status released		customer			
	title 1LE1501-2BC22-2AA4-Z B02+N03	document number					
© Siemens AG 2021	rev. 01	creation date 2021-04-21 09:55	language en	Page 1/2			

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV2222C

SIMOTICS SD - 225 M - IM B3 - 6p

Special design

B02	Acceptance test certificate 3.1 acc. to EN 10204	N03	Temperature class 155 (F), utilised to 155 (F), with increased cooling medium temperature
-----	--	-----	---

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>			
SIEMENS	document type datasheet	document status released		customer			
	title 1LE1501-2BC22-2AA4-Z B02+N03	document number					
© Siemens AG 2021	rev. 01	creation date 2021-04-21 09:55	language en	Page 2/2			