

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV1105B

SIMOTICS SD - 100 L - IM B3 - 4p

| | | |
|------------------|-----------------|-----------|
| Client order no. | Item-No. | Offer no. |
| Order no. | Consignment no. | Project |

Remarks

Electrical data

Safe Area

| U [V] | Δ / Y | f [Hz] | P [kW] | P [hp] | I [A] | n [1/min] | M [Nm] | η ³⁾ | | | $\cos\phi$ ³⁾ | | | I_A/I_N I_i/I_N | M_A/M_N T_i/T_N | M_K/M_N T_B/T_N | IE-CL |
|----------|--------------|-----------|-----------|-----------|----------|--------------|-----------|----------------------|------|------|--------------------------|------|------|------------------------|------------------------|------------------------|-------|
| | | | | | | | | 4/4 | 3/4 | 2/4 | 4/4 | 3/4 | 2/4 | | | | |
| 400 | Δ | 50 | 3.00 | -/- | 6.30 | 1425 | 20.0 | 81.5 | 82.6 | 81.5 | 0.85 | 0.78 | 0.65 | 5.4 | 2.4 | 2.6 | IE1 |
| 690 | Y | 50 | 3.00 | -/- | 3.60 | 1425 | 20.0 | 81.5 | 82.6 | 81.5 | 0.85 | 0.78 | 0.65 | 5.4 | 2.4 | 2.6 | IE1 |
| 460 | Δ | 60 | 3.45 | -/- | 5.90 | 1725 | 19.1 | 85.0 | 85.8 | 84.8 | 0.86 | 0.80 | 0.68 | 6.0 | 2.2 | 2.3 | IE1 |

| | | | | | |
|-----------------|----------|----|------|--------------|------------------------|
| IM B3 / IM 1001 | FS 100 L | kg | IP55 | IEC/EN 60034 | IEC, DIN, ISO, VDE, EN |
|-----------------|----------|----|------|--------------|------------------------|

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 9.76 s | 16.9 s

Mechanical data

| | | | | |
|---|---------------------------------|---------------------------------|----------------------------|---|
| Sound level (SPL / SWL) at 50Hz 60Hz | 60.0 / 72.0 dB(A) ²⁾ | 62.0 / 74.0 dB(A) ²⁾ | External earthing terminal | No |
| Moment of inertia | 0.0078 kg m ² | | Vibration severity grade | A |
| Bearing DE NDE | 6206 2Z C3 | 6206 2Z C3 | Insulation | 155(F) to 130(B) |
| bearing lifetime | | | Duty type | S1 |
| L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾ | 40000 h | 32000 h | Direction of rotation | bidirectional |
| Lubricants | Unirex N3 | | Frame material | cast iron |
| Regreasing device | No | | Coating (paint finish) | Standard paint finish C2 |
| Grease nipple | -/- | | Color, paint shade | RAL7030 |
| Type of bearing | Preloaded bearing DE | | Motor protection | (A) without (Standard) |
| Condensate drainage holes | Yes (standard) | | Method of cooling | IC411 - self ventilated, surface cooled |

Terminal box

| | | | |
|--------------------------|-----------|--------------------------------|---------------------|
| Terminal box position | top | Max. cross-sectional area | 4.0 mm ² |
| Material of terminal box | cast iron | Cable diameter from ... to ... | 11.0 mm - 21.0 mm |
| Type of terminal box | TB1 F01 | Cable entry | 2xM32x1,5 |
| Contact screw thread | M4 | Cable gland | 2 plugs |

Notes:
 I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
 1) L10mh according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

| | | | | |
|-------------------------------|---------------------|-------------------------------|-------------|---|
| responsible dep. DI MC LVM | technical reference | created by DT Configurator | approved by | <i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i> |
|-------------------------------|---------------------|-------------------------------|-------------|---|

| | | | | |
|-------------------|-----------------------------|-----------------------------------|----------------|-------------|
| SIEMENS | document type datasheet | document status released | customer | |
| | title 1LE1502-1AB53-4AA4 | document number | | |
| © Siemens AG 2021 | rev. 01 | creation date 2021-04-21 18:39 | language en | Page 1/1 |