



Figure similar

Data sheet for SIMOTICS T-1FW3

Article No. : 1FW3204-1AL72-6DA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

	P_N [kW]	M_N [Nm]	I_N [A]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	$n_{max, inv}$ [rpm]	M_0 [Nm]	I_0 [A]
ALM 400V	52.0	1,000	118	500	1,850	260	1,060	1,050	129
ALM 480V	57.0	900	106	600	1,850	260	1,060	1,050	129
SLM 400V	47.0	1,000	118	450	1,850	260	1,060	1,050	129
SLM 480V	58.0	1,000	118	550	1,850	260	1,060	1,050	129

Mechanical data

Motor type	Permanent-magnet synchronous motor
Shaft height	200
Cooling	Water cooling
Vibration severity grade	Grade A
Shaft and flange accuracy	Tolerance N (at normal running temperature)
Degree of protection	IP54
Design acc. to Code I	IM B14
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Anthracite grey RAL 7016 (Standard)
Type of the bearing	Normal (Standard)
Shaft extension	Hollow shaft
Encoder system	Incremental encoder sin/cos 1 Vpp 2048 S/R with C and D tracks (encoder IC2048S/R)
Encoder mounting system	Belt-mounted
Sound pressure level LpA(1m) motor rated load, tolerance + 3dB	73 dB ¹⁾

Limiting data

Max. permissible speed (mech.)	1,000 rpm
Max. permissible speed (inverter)	1,060 rpm
Maximum torque	1,850 Nm
Maximum current	260 A

Physical constants

Thermal time constant	14 min
Moment of inertia	7,000 kgcm ²
Weight (approx.)	225 kg

Connection

Type of electrical connection	Terminal box for power cable, connector for encoder signals and temperature sensor
Terminal box position	Transverse left
Power connection	Terminal box top

¹⁾ at 4 kHz rated pulse frequency at the rated operating point