

Data sheet for SIMOTICS S-1FK7




Figure similar

MLFB-Ordering data

1FK7022-5AK71-1LA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data			
Rated speed (100 K)	6000 rpm	Motor type	Permanent-magnet synchronous motor		
Number of poles	6	Motor type	Compact		
Rated torque (100 K)	0.6 Nm	Shaft height	28		
Rated current	1.4 A	Cooling	Natural cooling		
Static torque (60 K)	0.70 Nm	Radial runout tolerance	0.035 mm		
Static torque (100 K)	0.8 Nm	Concentricity tolerance	0.08 mm		
Stall current (60 K)	1.50 A	Axial runout tolerance	0.08 mm		
Stall current (100 K)	1.80 A	Vibration severity grade	Grade A		
Moment of inertia	0.280 kgcm ²	Connector size	1		
Efficiency	86.0 %	Degree of protection	IP64		
<th colspan="2">Physical constants</th>		Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
		Torque constant	0.46 Nm/A	Temperature monitoring	Pt1000 temperature sensor
		Voltage constant at 20° C	29.0 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
		Winding resistance at 20° C	4.20 Ω	Color of the housing	without
		Rotating field inductance	9.1 mH	Holding brake	without holding brake
		Electrical time constant	2.20 ms	Shaft extension	Feather key
		Mechanical time constant	1.70 ms	Encoder system	Encoder AM20DQ: absolute encoder 20 bits (resolution 1048576, encoder-internal 512 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
		Thermal time constant	18 min		
		Shaft torsional stiffness	3000 Nm/rad		
		Net weight of the motor	1.8 kg		




Figure similar

MLFB-Ordering data

1FK7022-5AK71-1LA0

Optimum operating point

Optimum speed	6000 rpm
Optimum power	0.4 kW

Limiting data

Max. permissible speed (mech.)	10000 rpm
Max. permissible speed (inverter)	10000 rpm
Maximum torque	3.4 Nm
Maximum current	8.0 A

Recommended Motor Module

Rated inverter current	3 A
Maximum inverter current	6 A
Maximum torque	2.65 Nm