

WITHDRAW. NON-AUT. CIRCUIT-B. WITHOUT GUIDE  
 FRAME 4-POLE,  
 SIZE I, IEC IN=1600A TO 690V,  
 AC50/60HZ ICU=55KA AT 500V REAR CONNECTION  
 HORIZONTAL

**General technical data:**

**Number of poles**

4

**Connections:**

**Arrangement of electrical connectors**

- for main current circuit

without guide frame

**Certificates/approvals:**

**General Product Approval**

**EMC**

**Declaration of Conformity**



CB



CCC



GOST



C-TICK



EG-Konf.

**Shipping Approval**



ABS



BUREAU  
VERITAS



DNV



GL



LRS

**other**

[other](#)

[Environmental  
Confirmations](#)

**Further information:**

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/lowvoltage/mall>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WWW/view/en/3WL1116-2A.45-..../all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3WL1116-2A.45-....](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1116-2A.45-....)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

last change:

Feb 9, 2013