

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3112A

SIMOTICS SD - 112 M - IM B3 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_i/I_N	M_A/M_N T_i/T_N	M_K/M_N T_B/T_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
230	Δ	50	4.00	-/-	12.80	2950	12.9	88.1	88.7	88.2	0.89	0.86	0.78	8.7	2.5	4.0	IE3
400	Y	50	4.00	-/-	7.40	2950	12.9	88.1	88.7	88.2	0.89	0.86	0.78	8.7	2.5	4.0	IE3
460	Y	60	4.55	-/-	7.20	3550	12.2	88.5	88.7	87.6	0.90	0.87	0.81	9.0	2.6	4.1	IE3
460	Y	60	3.70	5.00	6.00	3560	9.9	88.5	88.0	86.2	0.88	0.84	0.76	10.8	3.2	5.1	MG1
IM B3 / IM 1001			FS 112 M		45 kg	IP55	CC032A	IEC/EN 60034		IEC, EN, UL, CSA, NEMA MG1-12-12			kVA Code: P				

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 11.3 s | 14.9 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	69.0 / 81.0 dB(A) ²⁾	73.0 / 85.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0120 kg m ²		Vibration severity grade	A
Bearing DE NDE	6206 2Z C3	6206 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	cast iron
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	4.0 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 F01	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
 1) L10mh according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>			
SIEMENS	document type datasheet	document status released		customer			
	title 1LE1523-1BA22-2AA4	document number					
© Siemens AG 2021	rev. 01	creation date 2021-04-22 20:08	language en	Page 1/1			