



Figure similar

Data sheet for SIMOTICS T-1FW3

Article No. : 1FW3203-1FL72-5AA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

	P_N [kW]	M_N [Nm]	I_N [A]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	$n_{max, inv}$ [rpm]	M_0 [Nm]	I_0 [A]
ALM 400V	39.5	750	92	500	1,390	205	1,110	790	100
ALM 480V	42.5	680	83	600	1,390	205	1,110	790	100
SLM 400V	35.5	750	92	450	1,390	205	1,110	790	100
SLM 480V	43.0	750	92	550	1,390	205	1,110	790	100

Mechanical data

Motor type	Permanent-magnet synchronous motor
Shaft height	200
Cooling	Water cooling
Vibration severity grade	Grade A
Shaft and flange accuracy	Tolerance N (at normal running temperature)
Degree of protection	IP54
Design acc. to Code I	IM B14
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Anthracite grey RAL 7016 (Standard)
Type of the bearing	Normal (Standard)
Shaft extension	Hollow shaft
Encoder system	Absolute encoder 22 bit (resolution 4194304, internal 2048 S/R) + 12 bit multi-turn (traversing range 4096 revolutions) (encoder AM22DQ)
Encoder mounting system	Belt-mounted
Sound pressure level LpA(1m) motor rated load, tolerance + 3dB	73 dB ¹⁾

Limiting data

Max. permissible speed (mech.)	1,000 rpm
Max. permissible speed (inverter)	1,110 rpm
Maximum torque	1,390 Nm
Maximum current	205 A

Physical constants

Thermal time constant	12 min
Moment of inertia	4,900 kgcm ²
Weight (approx.)	182 kg

Connection

Type of electrical connection	Terminal box for power cable, connector for encoder signals and temperature sensor
Terminal box position	Transverse right
Power connection	Terminal box top

¹⁾ at 4 kHz rated pulse frequency at the rated operating point