



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : **1PH8135-4FG02-2AB1-Z**
U65

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	35.6	148.0	59.0	407	76.7	2,300	390	179.0	4,500	158.0	63	0.953	0.00	0.0
	BLM/SLM 400V	31.4	150.0	59.0	356	66.7	2,000	390	179.0	4,500	158.0	63	0.953	0.00	0.0
	ALM/BLM/SLM 480V	40.2	145.0	58.0	449	88.3	2,650	390	179.0	4,500	158.0	63	0.952	0.00	0.0

Mechanical data

Motor type	Permanent-magnet synchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP55
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Feather key with half key balancing
Encoder system	Absolut encoder 22 bit Singleturn + 12 bit Multiturn, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	10 min
Moment of inertia with brake	891 kgcm ²
Weight with brake (approx.)	166 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	left
Signal connection	DE
Terminal box designation	gk833

Cooling data and sound pressure level

Airflow, min.	0.09 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	140 Pa

Holding brake

Holding torque	140 ... 310 Nm ²⁾
Moment of inertia	141 kgcm ²
Power supply voltage	DC 24 V ± 10%
Coil current	6.3 A
Permissible brake work	15.5 kJ
Speed (Emergency Stop)	3,600 rpm
Number of emergency stops	2,000
Number of emergency stops per hour	3
Opening time	650 ms
Closing time	100 ms

Special design

U65 24 V DC holding brake

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

²⁾ Holding torque [Nm]: On motors with shaft height 100 ... 160, the holding torque can be gradually set using an adjusting ring within the value range specified (factory setting 100 % of the possible holding torque). The dynamic braking torque is approx. 70 % of the set holding torque.