



Figure similar

MLFB-Ordering data

6SL3121-1TE15-0AA4

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		Ambient conditions	
DC link voltage	DC 510 ... 720 V	Installation altitude (without derating)	1000 m (3281 ft)
Electronics power supply	DC 24 V -15 % / +20 %	Cooling ⁸⁾	External air cooling
Current demand, max.	0.85 A	Cooling air requirement	0.008 m ³ /s
DC-link current I _d	6.0 A	Ambient temperature	
Output current		During operation	
Rated value I _N	5.0 A	0 ... 40 °C (32 ... 104 °F)	
Base load current I _H	4.3 A	Connections	
For S6 duty (40%) I _{S6}	6.0 A	Motor end	
I _{max}	15.0 A	Version	connector (X1)
Type rating ²⁾		PE connection	M5 screw
Based on I _N	2.7 kW	Shield connecting kit	Integrated connection plug (X1)
Based on I _H	2.3 kW	Max. motor cable length	
Rated pulse frequency	4.00 kHz	Shielded	50 m (164 ft)
Current carrying capacity		Unshielded	75 m (246 ft)
DC link busbars ³⁾	100 A	Standards	
24 V busbars ⁴⁾	20 A	Compliance with standards	CE, cULus
DC link capacitance	110 µF	Safety Integrated	SIL 2 acc. to IEC 61508, PL d acc. to EN ISO 13849-1, Category 3 acc. to EN ISO 13849-1

MLFB-Ordering data

6SL3121-1TE15-0AA4



Figure similar

Mechanical data

Line side

Width	50.00 mm (1.97 in)
Height	380.00 mm (14.96 in)
Depth	226.00 mm (8.90 in)
Degree of protection	IP20 / UL open type
Type of construction	Booksize
Net weight	5.7 kg (12.57 lb)

General tech. specifications

Sound pressure level (1m)	60.0 dB
Power loss, max. ⁹⁾	0.04 kW

2) Rated output of a typical standard asynchronous motor at 400 V 3 AC

3) Possible with reinforced dc link busbar set 140 A (accessories).

4) If, when connecting several Line Modules and Motor Modules in series, the current carrying capacity exceeds 20 A, another 24 V DC connection is required using a 24 V terminal adapter (max. connectable cross-section 6 mm², max. protection 20 A).

8) Power units with intensified air cooling thanks to integrated fan

9) Power loss of the Motor Module with rated power including losses of the 24 V DC electronics power supply