

TRANSFORMER SITAS;  
 PHASES:1;  
 PN/PN(S6)(KVA):0,025 /0;  
 UPRI(V):400+/-5%;  
 USEC(V):24;  
 ISEC(A):1,04;  
 F(HZ):50...60;  
 VECTOR GR./SHIELD WNG.:li0 /0;  
 TA/ISOKL:40 /B;  
 IP00;  
 TYPE OF TERMINALS:SCREW/TAB CONNECTION;  
 INSTALLATION:MOUNTING RAILS;  
 EN 61558-2-6 >UL/CSA-RECOGNIZED< >SAFETY  
 ISOLATING TRANSFORMER<

**General technical details:**

<b>Product designation</b>		transformer SITAS
<b>product brand name</b>		SIDAC
<b>Operating apparent output / rated value</b>	V·A	25
<b>Efficiency</b>		0.74
<b>Manner of switching for transformers</b>		li0
<b>Verification of suitability</b>		CE / cRUus
<b>Product function</b>		
<ul style="list-style-type: none"> <li>• temperature surveillance</li> </ul>		No
<ul style="list-style-type: none"> <li>• isolation control</li> </ul>		No
<ul style="list-style-type: none"> <li>• short circuit and overload protection</li> </ul>		No
<b>Number of the protective coils</b>		0
<b>Relative short-circuit voltage</b>	%	17.6

**Inputs:**

<b>Phase number / of the inputs</b>		1
<b>Input voltage</b>		
<ul style="list-style-type: none"> <li>• _1 / rated value</li> </ul>	V	420
<ul style="list-style-type: none"> <li>• _2 / rated value</li> </ul>	V	400
<ul style="list-style-type: none"> <li>• _3 / rated value</li> </ul>	V	380
<b>Electrical input frequency</b>		
<ul style="list-style-type: none"> <li>• minimum</li> </ul>	Hz	50
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	Hz	60

**Outputs:**

<b>Phase number / of the outputs</b>		1
<b>Output voltage</b> • _1 / rated value	V	24
<b>Electrical output frequency</b> • maximum • minimum	Hz Hz	60 50

#### Ambient conditions:

<b>Thermal class / according to IEC 60085</b>		B
<b>Ambient temperature / rated value</b>	°C	40
<b>Protection class IP</b>		IP00

#### Mechanical design:

<b>Design of the electrical connection</b> • secondary side / for main current circuit • at the input / for main current circuit		screw-type terminals / tab terminals screw-type terminals / tab terminals
<b>Mounting type</b>		standard rail
<b>Construction form of the iron core</b>		EI 60/20
<b>Width</b>	m	0.062
<b>Height</b>	m	0.079
<b>Depth</b>	m	0.078

#### Certificates/approvals:

General Product Approval

Shipping Approval

other



GOST



PRS

[other](#)

#### Further information:

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrial-controls/mall>

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WWW/view/en/4AM2342-5AN00-0EB0/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=4AM2342-5AN00-0EB0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4AM2342-5AN00-0EB0)

last change:

Dec 5, 2011