

TS15X5 ST POK 0808

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration



Similar to illustration

The Klippon® POK enclosure range is made from a high-quality glass fibre reinforced polyester and is ideal for applications and environments where corrosion resistance, impact resistance and a high IP protection class are a requirement.

Key features of the extensive product range:

- Available in 17 sizes
- Two standard finishes (colours): grey (similar to RAL 7001 for industrial use) and black (similar to RAL 9011 for harsh environments, Ex)
- Cover with stainless steel screws in cross-head / slotted design
- Moulded gasket made of silicone or chloroprene
- Fixing holes outside the sealed area to ensure high ingress protection of IP66
- Impact resistance up to 7 Joules
- Mounting directly in the enclosure or using an internal mounting plate
- Direct wall mounting possible using fixing holes or mounting feet
- Fastening thread to attach mounting rails and plates
-
- Weidmüller can manufacture and supply this enclosure to match customer specifications - fitted with all necessary terminals and cable glands.

General ordering data

| | |
|------------|---|
| Version | Rail, TS 15, Width: 68 mm, without slot, Steel, galvanized, chromium-plated |
| Order No. | 8000003889 |
| Type | TS15X5 ST POK 0808 |
| GTIN (EAN) | 4050118652543 |
| Qty. | 20 pc(s). |

TS15X5 ST POK 0808

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|----------------|------------|-----------------|------------|
| Depth | 5 mm | Depth (inches) | 0.197 inch |
| Height | 15 mm | Height (inches) | 0.591 inch |
| Net weight | 15 g | Width | 68 mm |
| Width (inches) | 2.677 inch | | |

General information

| | | | |
|---------------------|-----------------|------------------|-----------------------------|
| Installation advice | Direct mounting | Integral fixing | Screwed |
| Material | Steel | Stamp dimensions | 4.5 x 20 mm |
| Standards | DIN EN 60715 | Surface finish | galvanized, chromium-plated |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC001285 | ETIM 7.0 | EC001285 |
| ECLASS 9.0 | 27-40-06-02 | ECLASS 9.1 | 27-40-06-02 |
| ECLASS 10.0 | 27-40-06-02 | ECLASS 11.0 | 27-40-06-02 |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|--------------------|--|
| Engineering Data | STEP |
| Brochure/Catalogue | Catalogues in PDF-format |