

## SLS 5.08/02/180FI SN OR BX

**Weidmüller Interface GmbH & Co. KG**


Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

### Product image



Similar to illustration

Male plugs with clamping-yoke screw wire-connect system. The male plugs provide space for labelling and can be coded.

### General ordering data

|              |  |
|--------------|--|
| Version      | PCB plug-in connector, male plug, 5.08 mm, Number of poles: 2, 180°, Clamping yoke connection, Clamping range, max.: 3.31 mm², Box |
| Order No.    | <a href="#">1846210000</a>   |
| Type         | SLS 5.08/02/180FI SN OR BX   |
| GTIN (EAN)   | 4032248362493  |
| Qty.         | 90 pc(s).  |
| Product data | IEC: 400 V / 21.5 A / 0.2 - 2.5 mm²<br>UL: 300 V / 14 A / AWG 26 - AWG 12  |
| Packaging    | Box  |

Creation date March 25, 2021 8:00:57 PM CET

## SLS 5.08/02/180FI SN OR BX

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Depth      | 22.3 mm | Depth (inches)  | 0.878 inch |
| Height     | 15.2 mm | Height (inches) | 0.598 inch |
| Net weight | 5.71 g  |                 |            |

## System Parameters

|  |  |                   |             |
|--|--|-------------------|-------------|
| Product family                               | OMNIMATE Signal - series BL/SL 5.08              |                   |             |
| Type of connection                           | Field connection                                 |                   |             |
| Wire connection method                       | Clamping yoke connection                         |                   |             |
| Pitch in mm (P)                              | 5.08 mm  |                   |             |
| Pitch in inches (P)                          | 0.2 inch   |                   |             |
| Conductor outlet direction                   | 180°   |                   |             |
| Number of poles                              | 2  |                   |             |
| L1 in mm                                     | 5.08 mm  |                   |             |
| L1 in inches                                 | 0.2 inch   |                   |             |
| Number of rows                               | 1  |                   |             |
| Pin series quantity                          | 1  |                   |             |
| Touch-safe protection acc. to DIN VDE 57 106 | finger-safe plugged/ back-of-hand-safe unplugged |                   |             |
| Volume resistance                            | ≤5 mΩ  |                   |             |
| Can be coded                                 | Yes  |                   |             |
| Stripping length                             | 7 mm   |                   |             |
| Clamping screw                               | M 2.5  |                   |             |
| Screwdriver blade                            | 0.6 x 3.5  |                   |             |
| Screwdriver blade standard                   | DIN 5264-A                                       |                   |             |
| Plugging cycles                              | 25   |                   |             |
| Plugging force/pole, max.                    | 4 N  |                   |             |
| Pulling force/pole, max.                     | 3 N  |                   |             |
| Tightening torque                            | Torque type                                      | Wire connection   |             |
|  | Usage information                                | Tightening torque | min. 0.4 Nm |
|  |  |                   | max. 0.5 Nm |
|  | Torque type                                      | Screw flange      |             |
| Usage information                            | Tightening torque                                | min. 0.2 Nm       |             |
|  |  | max. 0.25 Nm      |             |

## Material data

|                                       |          |                                       |                            |
|---------------------------------------|----------|---------------------------------------|----------------------------|
| Insulating material                   | PBT      | Colour                                | orange                     |
| Colour chart (similar)                | RAL 2000 | Insulating material group             | IIIa                       |
| Comparative Tracking Index (CTI)      | ≥ 200    | Insulation strength                   | ≥ 10 <sup>8</sup> Ω        |
| UL 94 flammability rating             | V-0      | Contact material                      | CuSn                       |
| Contact surface                       | tinned   | Layer structure of plug contact       | 4...8 μm Sn hot-dip tinned |
| Storage temperature, min.             | -40 °C   | Storage temperature, max.             | 70 °C                      |
| Operating temperature, min.           | -50 °C   | Operating temperature, max.           | 100 °C                     |
| Temperature range, installation, min. | -25 °C   | Temperature range, installation, max. | 100 °C                     |

## Conductors suitable for connection

|   |                      |
|---|----------------------|
| Clamping range, min.                    | 0.13 mm <sup>2</sup> |
| Clamping range, max.                    | 3.31 mm <sup>2</sup> |
| Wire connection cross section AWG, min. | AWG 26               |
| Wire connection cross section AWG, max. | AWG 12               |
| Solid, min. H05(07) V-U                 | 0.2 mm <sup>2</sup>  |

Creation date March 25, 2021 8:00:57 PM CET

## SLS 5.08/02/180FI SN OR BX

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

## Technical data

|   |                         |
|---|-------------------------|
| Solid, max. H05(07) V-U   | 2.5 mm <sup>2</sup>     |
| Flexible, min. H05(07) V-K  | 0.2 mm <sup>2</sup>     |
| Flexible, max. H05(07) V-K  | 2.5 mm <sup>2</sup>     |
| w. plastic collar ferrule, DIN 46228 pt 4, 0.2 mm <sup>2</sup> min. |                         |
| w. plastic collar ferrule, DIN 46228 pt 4, 2.5 mm <sup>2</sup> max. |                         |
| w. wire end ferrule, DIN 46228 pt 1, 0.2 mm <sup>2</sup> min.       |                         |
| w. wire end ferrule, DIN 46228 pt 1, 2.5 mm <sup>2</sup> max.       |                         |
| Plug gauge in accordance with EN 60999 a x b; ø                     | 2.8 mm x 2.0 mm; 2.4 mm |

| Clampable conductor                    | Cross-section for conductor connection | Type                         | fine-wired              |
|--|--|------------------------------|-------------------------|
|  |  | nominal                      | 0.5 mm <sup>2</sup>     |
| wire end ferrule                       | Stripping length                       | nominal                      | 6 mm                    |
|  |  | Recommended wire-end ferrule | <a href="#">H0.5/6</a>  |
| Cross-section for conductor connection | Type                                   | fine-wired                   |                         |
|  |  | nominal                      | 1 mm <sup>2</sup>       |
| wire end ferrule                       | Stripping length                       | nominal                      | 6 mm                    |
|  |  | Recommended wire-end ferrule | <a href="#">H1.0/6</a>  |
| Cross-section for conductor connection | Type                                   | fine-wired                   |                         |
|  |  | nominal                      | 1.5 mm <sup>2</sup>     |
| wire end ferrule                       | Stripping length                       | nominal                      | 7 mm                    |
|  |  | Recommended wire-end ferrule | <a href="#">H1.5/7</a>  |
| Cross-section for conductor connection | Type                                   | fine-wired                   |                         |
|  |  | nominal                      | 2.5 mm <sup>2</sup>     |
| wire end ferrule                       | Stripping length                       | nominal                      | 7 mm                    |
|  |  | Recommended wire-end ferrule | <a href="#">H2.5/7</a>  |
| Cross-section for conductor connection | Type                                   | fine-wired                   |                         |
|  |  | nominal                      | 0.75 mm <sup>2</sup>    |
| wire end ferrule                       | Stripping length                       | nominal                      | 6 mm                    |
|  |  | Recommended wire-end ferrule | <a href="#">H0.75/6</a> |

Reference text The outside diameter of the plastic collar should not be larger than the pitch (P). Length of ferrules is to be chosen depending on the product and the rated voltage.

### Rated data acc. to IEC

| tested acc. to standard   | IEC 60664-1, IEC 61984 | Rated current, min. number of poles (Tu=20°C)                         | 21.5 A            |
|---|------------------------|---|-------------------|
| Rated current, max. number of poles (Tu=20°C)                             | 16 A                   | Rated current, min. number of poles (Tu=40°C)                         | 18 A              |
| Rated current, max. number of poles (Tu=40°C)                             | 14 A                   | Rated voltage for surge voltage class / pollution degree II/2         | 400 V             |
| Rated voltage for surge voltage class / pollution degree III/2            | 320 V                  | Rated voltage for surge voltage class / pollution degree III/3        | 250 V             |
| Rated impulse voltage for surge voltage class/ pollution degree II/2      | 4 kV                   | Rated impulse voltage for surge voltage class/ pollution degree III/2 | 4 kV              |
| Rated impulse voltage for surge voltage class/ contamination degree III/3 | 4 kV                   | Short-time withstand current resistance                               | 3 x 1s with 120 A |

## SLS 5.08/02/180FI SN OR BX

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany


www.weidmueller.com

## Technical data

### Rated data acc. to CSA

|                                   |        |                                   |        |
|-----------------------------------|--------|-----------------------------------|--------|
| Rated voltage (Use group B / CSA) | 300 V  | Rated voltage (Use group D / CSA) | 300 V  |
| Rated current (Use group B / CSA) | 15 A   | Rated current (Use group D / CSA) | 10 A   |
| Wire cross-section, AWG, min.     | AWG 26 | Wire cross-section, AWG, max.     | AWG 12 |

### Rated data acc. to UL 1059

|                                       |   |                                       |        |
|---------------------------------------|---|---------------------------------------|--------|
| Institute (UR)                        |  | Certificate No. (UR)                  | E60693 |
| Rated voltage (Use group B / UL 1059) | 300 V   | Rated voltage (Use group D / UL 1059) | 300 V  |
| Rated current (Use group B / UL 1059) | 14 A  | Rated current (Use group D / UL 1059) | 10 A   |
| Wire cross-section, AWG, min.         | AWG 26  | Wire cross-section, AWG, max.         | AWG 12 |
| Reference to approval values          | Specifications are maximum values, details - see approval certificate.            |                                       |        |

### Packing

|           |        |            |        |
|-----------|--------|------------|--------|
| Packaging | Box    | VPE length | 30 mm  |
| VPE width | 135 mm | VPE height | 350 mm |

### Type tests

|                               |                |   |           |  |
|-------------------------------|----------------|---|-----------|--|
| Test: Durability of markings  | Standard       | VDE 0627 Tab. 7 item 3/6.86                   |           |  |
|                               | Test           | durability                                    |           |  |
|                               | Evaluation     | passed  |           |  |
| Test: Clampable cross section | Standard       | VDE 0609 part 1 06.83, EN 60947-1 03.91       |           |  |
|                               | Conductor type | Type of conductor and conductor cross-section | H05V-U0.5 |  |
|                               |                | Type of conductor and conductor cross-section | H05V-K0.5 |  |
|                               |                | Type of conductor and conductor cross-section | H05V-U2.5 |  |
|                               |                | Type of conductor and conductor cross-section | H05V-K2.5 |  |
|                               |                | Type of conductor and conductor cross-section | AWG 28    |  |
|                               |                | Type of conductor and conductor cross-section | AWG 14    |  |
| Evaluation                    | passed         |   |           |  |

**SLS 5.08/02/180FI SN OR BX**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data**

|   |                |   |           |  |
|---|----------------|---|-----------|--|
| Test for damage to and accidental loosening of conductors | Standard       | EN 60947-1/1991 section 8.2.4.3               |           |  |
|   | Requirement    | 0.3 kg  |           |  |
|   | Conductor type | Type of conductor and conductor cross-section | H05V-U0.5 |  |
|   |                | Type of conductor and conductor cross-section | H05V-K0.5 |  |
|   | Evaluation     | passed  |           |  |
|   | Requirement    | 0.7 kg  |           |  |
|   | Conductor type | Type of conductor and conductor cross-section | H07V-U2.5 |  |
|   |                | Type of conductor and conductor cross-section | H07V-K2.5 |  |
| Evaluation  | passed         |   |           |  |
| Pull-out test   | Standard       | EN 60947-1/1991 section 8.2.4.4               |           |  |
|   | Requirement    | ≥5 N  |           |  |
|   | Conductor type | Type of conductor and conductor cross-section | AWG 28/1  |  |
|   |                | Type of conductor and conductor cross-section | AWG 28/7  |  |
|   | Evaluation     | passed  |           |  |
|   | Requirement    | ≥50 N   |           |  |
|   | Conductor type | Type of conductor and conductor cross-section | H07V-U2.5 |  |
|   |                | Type of conductor and conductor cross-section | H07V-K2.5 |  |
| Type of conductor and conductor cross-section             |                | AWG 14/19                                     |           |  |
| Evaluation  | passed         |   |           |  |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002638    | ETIM 7.0    | EC002638    |
| ECLASS 9.0  | 27-44-03-09 | ECLASS 9.1  | 27-44-03-09 |
| ECLASS 10.0 | 27-44-03-09 | ECLASS 11.0 | 27-46-02-02 |

**SLS 5.08/02/180FI SN OR BX**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data****Important note**

|                |  |
|----------------|--|
| IPC conformity | Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request.   |
| Notes          | <ul style="list-style-type: none"> <li>• Additional colours on request</li> <li>• Rated current related to rated cross-section &amp; min. No. of poles.</li> <li>• Wire end ferrule without plastic collar to DIN 46228/1</li> <li>• Wire end ferrule with plastic collar to DIN 46228/4</li> <li>• P on drawing = pitch</li> <li>• Rated data refer only to the component itself. Clearance and creepage distances to other components are to be designed in accordance with the relevant application standards.</li> <li>• Long term storage of the product with average temperature of 50 °C and average humidity 70%, 36 months</li> </ul> |

**Approvals**

Approvals




|                       |         |
|-----------------------|---------|
| ROHS                  | Conform |
| UL File Number Search | E60693  |


**Downloads**

|   |   |
|---|---|
| Approval/Certificate/Document of Conformity | <a href="#">Declaration of the Manufacturer</a> |
| Engineering Data                            | <a href="#">STEP</a>                            |
| Engineering Data                            | <a href="#">WSCAD</a>                           |


**Dimensional drawing**




**Graph**



**Graph**






**Graph**



WEITERGABE SOWIE VERVIELFÄLTIGUNG DIESES DOKUMENTS, VERWERTUNG UND MITTEILUNG SEINES INHALTS SIND VERBOTEN, SOWEIT NICHT AUSDRUECKLICH GESTATET.  
 ZUWIDERHANDLUNGEN VERPFLICHTEN ZU SCHADENSERSATZ. ALLE RECHTE FUER DEN FALL DER PATENT-, GEBRAUCHSMUSTER- ODER GESCHWACKMUSTEREINTRAGUNG VORBEHALTEN.  
 THE REPRODUCTION, DISTRIBUTION AND UTILIZATION OF THIS DOCUMENT AS WELL AS THE COMMUNICATION OF ITS CONTENTS TO OTHERS WITHOUT EXPLICIT AUTHORIZATION IS PROHIBITED.  
 OFFENDERS WILL BE HELD LIABLE FOR THE PAYMENT OF DAMAGES. ALL RIGHTS RESERVED IN THE EVENT OF THE GRANT OF A PATENT, UTILITY MODEL OR DESIGN.

DIE DEUTSCHE VERSION IST VERBINDLICH  
THE GERMAN VERSION IS BINDING



|    |         |           |
|----|---------|-----------|
| n  | L1 [mm] | L1 [Inch] |
| 24 | 116,84  | 4,600     |
| 23 | 111,76  | 4,400     |
| 22 | 106,68  | 4,200     |
| 21 | 101,60  | 4,000     |
| 20 | 96,52   | 3,800     |
| 19 | 91,44   | 3,600     |
| 18 | 86,36   | 3,400     |
| 17 | 81,28   | 3,200     |
| 16 | 76,20   | 3,000     |
| 15 | 71,12   | 2,800     |
| 14 | 66,04   | 2,600     |
| 13 | 60,96   | 2,400     |
| 12 | 55,88   | 2,200     |
| 11 | 50,80   | 2,000     |
| 10 | 45,72   | 1,800     |
| 9  | 40,64   | 1,600     |
| 8  | 35,56   | 1,400     |
| 7  | 30,48   | 1,200     |
| 6  | 25,40   | 1,000     |
| 5  | 20,32   | 0,800     |
| 4  | 15,24   | 0,600     |
| 3  | 10,16   | 0,400     |
| 2  | 5,08    | 0,200     |

SHOWN: SLS 5.08/04/180FI

For the mounting of PCBs, it should be noted that the rated data relates only to the PCB components alone.  
 The necessary creepage and clearance paths must be observed in connection with the respective applicant in accordance to IEC 664 / VDE 0110.  
 The current-carrying capacity and pitch tolerance is to be determined according to DIN IEC 326 part 3 very fine.

Weidmüller PCB components are tested to the DIN EN 61984 standard, and are valid for its field of application.  
 Provided that the components are used to the intended purpose, all requirements with respect to the occurring of electrical, mechanical, thermic and corrosive stress will be satisfied.

|   |   |  |                                 |  |
|---|---|--|---------------------------------|--|
|   | <b>METRIC TOLERANCES:</b><br>X. = ±0.3<br>X.X = ±0.1<br>X.XX = ±0.05                                    |  | 53611/5<br>06.10.10 HERTEL_S 01 | CAT.NO.:<br><b>C 34205 03</b>  |
|   | DRAWN 26.03.2007 HERTEL_S<br>RESPONSIBLE HERTEL_S<br>CHECKED 06.10.2010 HECKERT_M<br>APPROVED HECKERT_M |  | <b>Weidmüller</b>               | DRAWING NO. SHEET 02 OF 02 SHEETS<br>ISSUE NO.   |
| SCALE: 2:1<br>SUPERSEDES:<br>SUPERSEDED BY: |   | DATE NAME<br>26.03.2007 HERTEL_S<br>06.10.2010 HECKERT_M |                                 | <b>SLS 5.08/././180 F(FI)..</b><br>STIFTLISTE<br>PIN HEADER<br>PRODUCT FILE: SLS 5.08 7314 |



