

# SIEMENS

## Product data sheet

**6AV6371-1BE06-2AX0**


WINCC POWERPACK RT 128/1024 FOR SIMATIC  
WINCC V6.2,  
RT LICENSE W/O VERSION CONVERSION FROM  
128 TO 1024 POWER TAGS,  
SINGLE LICENSE

General information	
Multi-user system	
Multiuser capability	Yes
Number of servers, max.	12
Number of clients for server without operator console, max.	32
Web clients	Yes
Operator control and monitoring	
Object block library	Yes ; integrated
With alarm logging system (incl. buffer and acknowledgment)	No ; integrated
Report system/log system	Yes
SQL database	Yes ; integrated
Process diagnostics	No
Sector-specific and technological expansions	No
Recipes	

User archive/recipe management	No
<b>Interfaces</b>	
Programming interfaces	Yes
OPC-DA interface, Server	Yes
OPC-DA interface, Client	Yes
<b>Hardware requirements</b>	
Processor clock frequency, min.	1 GHz
Main memory, min.	1000 Mbyte
<b>Configuration</b>	
Max. number of multiusers configuration	32
Online configuration	Yes
<b>Script languages (Runtime)</b>	
Visual Basic	Yes
other	Yes
<b>Know-how protection</b>	
Password protection	Yes
<b>Languages</b>	
<b>Configuration languages</b>	
Number of configuration languages	70
Status	Jul 17, 2012