

SIEMENS

Product data sheet

6AV6371-2BD07-0AX0


WINCC POWERPACK RT 128/512 FOR SIMATIC
WINCC V7.0,
RT LICENSE W/O VERSION CONVERSION FROM
128 TO 512 POWER TAGS,
SINGLE LICENSE

General information	
Multi-user system	
Multiuser capability	Yes
Number of servers, max.	12
Number of clients for server without operator console, max.	32
Web clients	Yes
Operator control and monitoring	
Object block library	Yes ; integrated
With alarm logging system (incl. buffer and acknowledgment)	Yes ; integrated
Report system/log system	Yes
SQL database	Yes ; integrated
Process diagnostics	No
Sector-specific and technological expansions	No
Recipes	

User archive/recipe management	No
Interfaces	
Programming interfaces	Yes
OPC-DA interface, Server	Yes
OPC-DA interface, Client	Yes
Hardware requirements	
Processor clock frequency, min.	1 GHz
Main memory, min.	1000 Mbyte
Configuration	
Max. number of multiusers configuration	32
Online configuration	Yes
Script languages (Runtime)	
Visual Basic	Yes
other	Yes
Know-how protection	
Password protection	Yes
Languages	
Configuration languages	
Number of configuration languages	70
Status	Jul 17, 2012