



LOGO!POWER 12 V STABILIZED POWER SUPPLY INPUT: 100-240 V AC (110-300 V DC) OUTPUT: 12 V/1.9 A DC

## Technical specifications

Product	LOGO!Power
Power supply, type	12 V/1.9 A
<b>Input</b>	
Input	1-phase AC or DC
Rated voltage value $V_{in}$ rated	100 ... 240 V
Voltage range	85 ... 264 V
Input voltage / at DC	110 ... 300 V
Wide-range input	Yes
Overtoltage resistance	$2.3 \times V_{in}$ rated, 1.3 ms
Mains buffering at $I_{out}$ rated, min.	40 ms
Mains buffering	at $V_{in} = 187$ V
Rated line frequency	50 / 60 Hz
Rated line range	47 ... 63 Hz
Input current / at nominal level of the input voltage 120 V	0.53 A
Input current / at nominal level of the input voltage 230 V	0.3 A
Switch-on current limiting (+25 °C), max.	25 A
$I^2t$ , max.	0.8 A <sup>2</sup> ·s
Built-in incoming fuse	internal
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 16 A, characteristic B or from 10 A, characteristic C

<b>Output</b>	
Output	Controlled, isolated DC voltage
Rated voltage $V_{out}$ DC	12 V
Total tolerance, static $\pm$	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	1.5 %
Residual ripple peak-peak, max.	200 mV
Residual ripple peak-peak, typ.	10 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	300 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	20 mV
Adjustment range	10.5 ... 16.1 V
Product feature / output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for output voltage OK
On/off behavior	No overshoot of $V_{out}$ (soft start)
Startup delay, max.	0.5 s
Voltage rise, typ.	10 ms
Rated current value $I_{out}$ rated	1.9 A
Current range	0 ... 1.9 A
• Note	1.9 A up to +55 °C, 1.3 A up to +70 °C
delivered active power / typ.	23 W
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2
<b>Efficiency</b>	
Efficiency at $V_{out}$ rated, $I_{out}$ rated, approx.	80 %
Power loss at $V_{out}$ rated, $I_{out}$ rated, approx.	5 W
<b>Closed-loop control</b>	
Dynamic mains compensation ( $V_{in}$ rated $\pm 15$ %), max.	0.2 %
Dynamic load smoothing ( $I_{out}$ : 10/90/10 %), $U_{out} \pm$ typ.	3 %
Load step setting time 10 to 90%, typ.	1 ms
Load step setting time 90 to 10%, typ.	1 ms
<b>Protection and monitoring</b>	
Output overvoltage protection	Yes, according to EN 60950
Current limitation, typ.	2.8 A
Characteristic feature of the output / short-circuit protected	Yes
Short-circuit protection	Constant current characteristic
Enduring short circuit current / Effective level / maximum	3.6 A
Overload/short-circuit indicator	-
<b>Safety</b>	


Primary/secondary isolation	Yes
Potential separation	Safety extra-low output voltage U <sub>out</sub> acc. to EN 60950-1 and EN 50178
Protection class	Class II (without protective conductor)
CE mark	Yes
UL/CSA approval	Yes
UL/cUL (CSA) approval	cULus-listed (UL 508, CSA C22.2 No. 107.1), File E197259; cURus-recognized (UL 60950, CSA C22.2 No. 60950), File E151273
Explosion protection	ATEX (EX) II 3G Ex nA IIC T3; cCSAus (CSA E60079, UL 60079), Class I, Div. 2, Group ABCD, T4
FM approval	Class I, Div. 2, Group ABCD, T4
CB approval	Yes
Marine approval	GL, ABS
Degree of protection (EN 60529)	IP20
<b>EMC</b>	
Emitted interference	EN 55022 Class B
Supply harmonics limitation	not applicable
Noise immunity	EN 61000-6-2
<b>Operating data</b>	
Ambient temperature / in operation	-20 ... +70 °C
• Note	with natural convection
Ambient temperature / on transport	-40 ... +85 °C
Ambient temperature / in storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, no condensation
<b>Mechanics</b>	
Connection technology	screw-type terminals
Connections / Supply input	L, N: 1 screw terminal each for 0.5 ... 2.5 mm <sup>2</sup> single-core/finely stranded
Connections / Output	+, -: 2 screw terminals each for 0.5 ... 2.5 mm <sup>2</sup>
Connections / Auxiliary	-
Width / of the housing	54 mm
Height / of the housing	90 mm
Depth / of the housing	55 mm
Installation width	54 mm
Mounting height	130 mm
Weight, approx.	0.17 kg
Product feature / of the housing / housing for side-by-side mounting	Yes
Type of mounting / wall mounting	No
Type of fixing / cap rail mounting	Yes
Type of mounting / S7-300 rail mounting	No

Installation

Snap onto DIN rail EN 60715 35x7.5/15

Other information

Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)



letzte Änderung:

Jul 25, 2012