

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Product image







Building installation wiring

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

General ordering data

Version	Accessories, Clamping yoke for busbar, Rated cross-section: Clamping yoke, Feed-through (bushing)
Order No.	0556800000
Туре	ZB 16/6
GTIN (EAN)	4008190007751
Qty.	50 pc(s).



Material

Weidmüller Interface GmbH & Co. KG

silver

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	30.7 mm	Depth (inches)	1.209 inch
Height	12.5 mm	Height (inches)	0.492 inch
Net weight	6.78 g	Width	10 mm
Width (inches)	0.394 inch		
Temperatures			
Temperatures Operating temperature range	For operating temperature		
	For operating temperature range see EC Design Test Certificate / IEC Ex-		

Colour

Steel



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Rating data IECEx/ATEX

Certificate No. (ATEX)	DEMKO03ATEX136028U	ATEX certificate	DEMKO03ATEX136028U_e
Certificate No. (IECEX)	IECEXULD13.0005U	Wire cross section max. (ATEX)	16 mm²
Wire cross section max. (IECEX)	16 mm²	Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex- Certificate of Conformity
Marking FN 60079-7	-	Ex 2014/34/FU label	
Marking EN 60079-7 Safety notice	Ex eb II C Gb Installation instructions: The potential equalisation (PE) rail modules are suitable for use in housings in atmospheres with flammable gases and dust. For use in areas with flammable gases, these housings must meet the requirements of EN 60079-0 and EN 60079-7. For use in areas with flammable dust, these housings must meet the requirements of EN 60079-0 and EN 60079-3.1. When combined with other terminal block ranges and sizes, and when other accessories are used, you must comply with the clearance and creepage distances given. Regarding accessory use, the manufacturer's instructions must be followed. List of restrictions: The PE rail modules are considered one component, with Ex marking when used with the busbar holders of type SH and WEW. When used independently, the above named components	Ex 2014/34/EU label	II 2 G D
	above named components are not covered by this certificate.		

Version	for busbar 6 x 6 mm	

Additional technical data

Installation advice	Feed-through (bushing)	Type of mounting	when screwed in
CSA rating data			
Contitionts No. (CCA)	12400 227	Mina and a satisfactor was a CCA	0.404/0
Certificate No. (CSA) Wire cross section min. (CSA)	12400-237 12 AWG	Wire cross section max. (CSA)	6 AWG

Creation date March 22, 2021 10:52:17 AM CET



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Conductors for clamping (rated connection)

Clamping screw		Connection cross-section, stranded,	
	M 4	max.	25 mm²
Connection cross-section, stranc	led, min. 16 mm²	Stripping length	12 mm
Tightening torque, min.	2.6 Nm	Type of connection	Clamping yoke
Wire connection cross section, f	inely	Wire connection cross-section	n, solid
stranded, max.	16 mm²	core, max.	16 mm²
Wire connection cross-section, s	olid		
core, min.	2.5 mm ²		

General

Classifications

ETIM 6.0	EC002848	ETIM 7.0	EC002848
ECLASS 9.0	27-14-11-92	ECLASS 9.1	27-14-11-92
ECLASS 10.0	27-14-11-92	ECLASS 11.0	27-14-11-46

Approvals

Approvals



ROHS	Conform
Downloads	
Approval/Certificate/Document of Conformity	Attestation of Conformity ATEX Certificate IECEx Certificate
Engineering Data	STEP
Engineering Data	<u>EPLAN</u>
User Documentation	Installation Instruction StorageConditionsTerminalBlocks